Lifting Solutions Group
Axel Johnson International

Open Wedge Socket CP Green Pin® G-6413

Product information

The Green Pin® Open Wedge Socket CP is an open wedge socket with a cotter (split) pin. The socket is made from high tensile steel, while galvanization ensures its long-term durability. Green Pin® Open Wedge Socket CP is available for wire rope with a diameter from 7-8 up to 81-86 mm.

Certification on request: 2.1, 2.2, 3.1

... *Read more*

Material: high tensile steel
Marking: According to standard, CE-marked
Temperature range: -20°C up to +200°C
Finish: hot dipped galvanized
Standard: EN 13411-6

© October 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Open Wedge Socket CP Green Pin® G-6413

Blueprint



Technical data

Part code	Rope Ø range mm	MBL ton	Finish	Number	length a mm	width inside d mm	a mm	b mm	c mm	d mm	e mm	f mm	g mm	Weight kg
121500800242	7-8	8	Galvanized	0.25	128	18	128	110	51	18	16	9	36	0.79
121501000242	9-10	12	Galvanized	0.5	165	20.5	165	142	62	20.5	21	11	46	1.5
121501300242	11-13	20	Galvanized	1	175	25	175	146	66	25	25	12	57	2.4
121501600242	14-16	25	Galvanized	2	211	31	211	176	82	31	30	15	70	4
121501900242	18-19	40	Galvanized	3	252	38	252	212	95	38	35	16	80	7.4
121502200242	20-22	55	Galvanized	4	288	44	288	240	110	44	41	19	95	11
121502600242	24-26	75	Galvanized	5	329	51	329	274	130	51	51	22	110	16
121502900242	27-29	90	Galvanized	6	375	57	375	310	144	57	57	25	130	22
121503200242	30-32	110	Galvanized	7	423	63	423	350	155	63	64	28	146	31
121503600242	34-36	125	Galvanized	8	474	69	474	400	163	69	64	28	148	39
121503900242	37-39	150	Galvanized	9	527	76	527	450	178	76	70	30	153	50
121504200242	40-42	170	Galvanized	10	580	76	580	500	187	76	76	33	160	66
121504800242	43-48	225	Galvanized	11	650	89	650	550	213	89	89	39	186	96
121505200242	49-52	280	Galvanized	12	745	101	745	640	240	101	95	46	194	130
121505800242	54-58	360	Galvanized	13	785	114	785	660	275	114	108	54	250	180
121506800242	60-68	425	Galvanized	14	970	127	970	835	300	127	121	60	270	275
121507600242	72-76	460	Galvanized	15	1,150	146	1,150	1,000	355	146	133	76	300	440
121508600242	81-86	625	Galvanized	16	1,252	159	1,310	1,160	375	159	140	79	300	510

© October 2026 - All Rights Reserved