



Metric Swivel Hoist Rings Crosby HR-125M

Product information

Features:

- The Working Load Limit and Recommended Torque value are permanently stamped into each washer.
- Washer is color coded for easy identification: Silver - Metric thread.
- Bolt specification is a Grade 12.9 Alloy socket head cap screw to DIN 912.
- Designed to be used with ferrous workpiece only.
- BOLT SIZE IDENTIFICATION: The size of the bolt will be stated as in the blueprint. Illustration shows meaning of each dimension given.

Safety factor: 5:1

| Part Code | Torque Nm | WLL ton 4:1 | WLL ton 5:1 | A mm | B mm | C mm | D mm | E mm | ØF mm | G mm | H mm | Weight (kg) | Delivery time |
|-----------|-----------|-------------|-------------|--------------|------|------|------|------|-------|------|------|-------------|---------------|
| -- | 10 | 0.5 | 0.4 | M8x1,25x40 | 16.9 | 69.9 | 24.6 | 11.8 | 8.5 | 47.5 | 29.9 | 0.17 | 2 |
| 05B0720 | 16 | 0.55 | 0.45 | M10x1,50x40 | 16.9 | 69.9 | 24.6 | 11.8 | 8.5 | 47.5 | 28.1 | 0.18 | 2 |
| 05B0730 | 38 | 1.3 | 1.05 | M12x1,75x50 | 16.9 | 123 | 49.8 | 22.3 | 17.5 | 85.1 | 60.4 | 1.05 | 2 |
| 05B0740 | 81 | 2.4 | 1.9 | M16x2,00x60 | 26.9 | 123 | 49.8 | 22.3 | 17.5 | 85.1 | 56.3 | 1.11 | 2 |
| 05B0750 | 136 | 2.7 | 2.15 | M20x2,50x65 | 31.9 | 123 | 49.8 | 22.3 | 17.5 | 85.1 | 52.3 | 1.17 | 2 |
| 05B0755 | 136 | 3.75 | 3 | M20x2,50x75 | 27.8 | 167 | 75.2 | 34.7 | 25.4 | 124 | 76.6 | 3.09 | 2 |
| 05B0760 | 312 | 5.25 | 4.2 | M24x3,00x80 | 32.8 | 167 | 75.2 | 34.7 | 25.4 | 124 | 70.5 | 3.21 | 2 |
| 05B0765 | 637 | 8.75 | 7 | M30x3,50x120 | 61.7 | 222 | 94.2 | 44.5 | 30.5 | 157 | 102 | 6.53 | 2 |
| -- | 1,005 | 13.75 | 11 | M36x4,00x150 | 54 | 318 | 120 | 60.7 | 44.5 | 215 | 142 | 16.8 | 2 |
| -- | 1,005 | 15.6 | 12.5 | M42x4,50x160 | 64 | 318 | 120 | 60.7 | 44.5 | 215 | 136 | 17.4 | 2 |
| -- | 1,350 | 16.9 | 13.5 | M48x5,00x160 | 74 | 318 | 120 | 60.7 | 44.5 | 215 | 130 | 18 | 2 |

Blueprint

