



## Wedge Socket Crosby S-421T

### Product information

#### Features:

- Secures the tail or “dead end” of the wire rope to the wedge, thus eliminates loss or “Punch out” of the wedge.
- Eliminates the need for an extra piece of rope, and is easily installed.
- The TERMINATOR™ wedge eliminates the potential breaking off of the tail due to fatigue.
- The tail, which is secured by the base of the clip and the wedge, is left undeformed and available for reuse.
- Incorporates Crosby’s patented QUIC-CHECK™ “Go” and “No-Go” feature cast into the wedge.
- Utilises standard Crosby Red-U-Bolt wire rope clip.
- Generates a minimum efficiency of 80% based on the catalogue breaking strength of the wire rope.
- Pin diameter and jaw opening allows wedge and socket to be used in conjunction with open swage and spelter sockets.

Wedge sockets meet the performance requirements of Federal Specification RR-S-550F, Type C, except those provisions required of the contractor.

**Material:** Cast Steel.

**Marking:** According to standard, ID code and Manufacturer's symbol.

**Finish:** Painted.

**Standard:** EN 13411-6

**Safety factor:** 5:1

Part code	Rope Ø range mm	Finish	A,	B,	C +/- 2.29 mm	D,	G,	H,	J* mm	K* mm	L	P mm	R mm	S mm	T mm	U mm	V mm	Weight kg	Delivery time
121501000115	9-10	Painted	145	69,1	20,6	20,6	35,1	77,7	198	47,8	22,4	39,6	11,2	54,1	11,2	31,8	35,1	1.44	-
121501300115	11-13	Painted	175	88,1	25,4	25,4	41,1	95,5	226	32,0	26,9	49,3	12,7	65,0	13,5	44,5	47,8	2.79	3
121501600115	14-16	Painted	210	109	31,8	30,2	53,8	114	273	50,5	31,0	57,2	14,2	82,6	17,5	51,0	55,5	4.4	3
121501900115	18-19	Painted	251	130	38,1	35,1	62,0	134	314	61,2	35,6	66,8	16,8	92,2	19,8	59,5	65,0	6.58	3
121502200115	20-22	Painted	286	149	44,5	41,4	68,5	156	365	63,0	42,4	79,5	19,1	109	22,4	68,5	74,5	9.75	-
121502600115	24-26	Painted	325	161	51,0	51,0	74,7	177	414	77,2	51,0	95,5	22,4	119	26,2	73,0	83,5	13.9	3
121502800115	28	Painted	365	176	57,0	57,0	84,0	194	466	65,0	57,0	108	25,4	138	27,9	82,6	90,5	20.5	-
121503200115	30-32	Painted	415	222	66,5	63,5	90,5	239	520	74,7	59,5	114	26,9	156	30,2	117	125	29.4	-

## Blueprint

