



Stay rope



Spiral Strand 1x19 Stainless

Product information



Typical applications: Wire rope for rigging, stays and controls.

Design: Right- or left-handed.

Rope construction: 1x19

Material: AISI 316

Marking: According to standard

Standard: EN 12385-10

except material

Fill factor: 0.76

Part code	Rope diameter mm	Tensile strength N/mm ²	Finish	Rope lay	Min. breaking force kN	Steel area mm ²	Lubrication	Weight kg/100m
108100101620078	1	1,570	Stainless	S	0.82	-	No-Lube	0.5
108100102620078	1	1,570	Stainless	Z	0.82	-	No-Lube	0.5
108100201620078	2	1,570	Stainless	S	3.3	-	No-Lube	2
108100202620078	2	1,570	Stainless	Z	3.3	-	No-Lube	2
108100301620078	3	1,570	Stainless	S	7.42	-	No-Lube	4.5
108100401620078	4	1,570	Stainless	S	13.2	-	No-Lube	7.9
108100402620078	4	1,570	Stainless	Z	13.2	-	No-Lube	7.9
108100501620078	5	1,570	Stainless	S	20.6	-	No-Lube	12.4
108100502620078	5	1,570	Stainless	Z	20.6	-	No-Lube	12.4
108100601620078	6	1,570	Stainless	S	29.7	-	No-Lube	17.8
108100602620078	6	1,570	Stainless	Z	29.7	-	No-Lube	17.8
108100701620078	7	1,570	Stainless	S	40.4	-	No-Lube	24.3
108100702620078	7	1,570	Stainless	Z	40.4	-	No-Lube	24.3
108100801620078	8	1,570	Stainless	S	52.8	-	No-Lube	31.7
108100802620078	8	1,570	Stainless	Z	52.8	-	No-Lube	31.7
108101001620078	10	1,570	Stainless	S	82.5	-	No-Lube	49.5
108101002620078	10	1,570	Stainless	Z	82.5	-	No-Lube	49.5
108101201620078	12	1,570	Stainless	S	119	-	No-Lube	71.3
108101202620078	12	1,570	Stainless	Z	119	-	No-Lube	71.3