

Web Sling Connector X-016



Product information

At least 25% greater WLL than traditional Grade 8 products.
 Proof Load tested at 2.5 times the WLL with certification for each batch manufactured.
 Fatigue rated to 20,000 cycles at 1.5 times the WLL.
 Tempering temperature minimum 400°C

Material: Quenched and Tempered Alloy Steel.

Marking: According to standard, Type, manufacturer ID, traceability.

Temperature range: -40° up to +200°C (without reduction in WLL).

Finish: Blue painted.

Standard: EN 1677-1

Safety factor: 4:1

Grade: 10

| Part Code | Chain diameter mm | WLL ton | A mm | B mm | D mm | K mm | W mm | Weight kg |
|---------------|----------------------|------------|---------|---------|---------|---------|---------|--------------|
| 11.06X-016-06 | 6 | 1.4 | 15 | 17 | 7 | 56 | 39 | 0.2 |
| 11.06X-016-07 | 7-8 | 2.5 | 18 | 23 | 9 | 63 | 39 | 0.3 |
| 11.06X-016-10 | 10 | 4 | 25 | 27 | 11 | 77 | 46 | 0.6 |
| 11.06X-016-13 | 13 | 6.7 | 30 | 37 | 16 | 97 | 53 | 1.1 |
| 11.06X-016-16 | 16 | 10 | 36 | 39 | 19 | 114 | 66 | 2 |
| 11.06X-016-20 | 20 | 16 | 42 | 46 | 22 | 132 | 79 | 3.2 |
| 11.06X-016-22 | 22 | 19 | 49 | 59 | 24 | 188 | 124 | 7.7 |

Blueprint

