

Aluminium Hollow Plunger Cylinder HAHC H

Product information



Holmatro aluminum hollow plunger cylinders (HAHC) - Spring or hydraulic return

Unique specifications:

- Up to 60% lighter compared to steel cylinders - easy & ergonomic
- Compact design and a lower build-in
- Suitable for pulling, lifting, tensioning in all positions
- Duo power ring; a combination of a superior seal and an extremely strong composite bearing for a longer life span
- The plunger is coated with a hardened anodized layer, which makes it extremely wear & corrosion resistant

Standard supplied with:

- High flow female coupler A118
- Hollow saddle; prevents damage to the plunger
- Larger cylinders are equipped with foldable handles for easy carrying and positioning

Also available:

- Hydraulic pump units 700bar to control your system
- Hydraulic hoses 700bar
- System components to complete your hydraulic system

Material: Aluminium

Part code	Code	WLL ton	stroke length mm	Closed height mm	required oil cc	Weight kg
5211100112381	HAHC100H5	100	50	229	415	28.2
5211100112382	HAHC100H10	100	100	279	831	34
5211100112383	HAHC100H15	100	150	329	1,246	39.7
5211100112384	HAHC100H20	100	200	379	1,661	45.4
5211100112385	HAHC100H25	100	250	429	2,076	51.2
5211100112386	HAHC150H5	150	50	247	471	41
5211100112387	HAHC150H10	150	100	297	942	48.5
5211100112388	HAHC150H15	150	150	347	1,414	56
5211100112389	HAHC150H20	150	200	397	1,885	63.5
5211100112390	HAHC150H25	150	250	447	2,356	71

Blueprint

