

HPJ S Hydraulic Pulling Cylinder

Product information



Holmatro pulling cylinders (HPJ) – Spring return

Unique specifications:

- Compact
- Suitable for pulling, lifting, tensioning in all positions
- Protected against over pressure; A418 valve

Standard supplied with:

- High flow female coupler A118, with pressure relief valve A418

Accessories:

- Pulling eyes (art. No 100.181.051) and clevis eyes (art. No 100.181.056): 2 of both per cylinder = mandatory
- Protection spring (art. No. 100.581.160) = optional

Also available:

- Accessories
- Hydraulic pump units 700bar to control your system
- Hydraulic hoses 700bar
- System components to complete your hydraulic system

Material: Steel

Note: Protection Spring, Pulling eyes and clevis eyes to be ordered separately (2 pcs per cylinder)

Part code	Code	WLL ton	stroke length mm	required oil cc	A,	B,	C,	D2 mm	F,	G,	H tread size	J,	P mm	Weight kg
5211100131001	HPJ 11 S 15	11	150	236	320	92	40	85	250	470	M38x1.5	30	38	11.5
5211100131011	HPJ 30 S 15	30	150	623	470	118	40	85	380	620	M38x1.5	40	44	26
5211100131021	HPJ 60 S 15	60	150	1,272	530	157	60	85	400	680	M54x1.5	60	52	45

Blueprint

