



## Eyebolts - Collared BS 4278:1984

### Product information

**Design:** Warning! Safe working loads quoted refer to the load being applied vertically. Eyebolts need to be down rated when side loading occurs. Sizes marked \* are additional and proportional to the specification.

Also available with UNC, UNF, BSF threads.

**Safety factor:** 4:1.

Part Code	WLL ton	Stock Code bsw	Stock Code unc	A mm	B mm	D mm	E mm	F mm	G mm	H mm	Weight (kg)	Delivery time
--	0.1	-	-	1/4	22	7	15	9	20	18	0.06	2
--	0.25	05B0300	05B0360	3/8	22	7	15	9	20	18	0.06	2
--	0.5	05B0310	05B0370	1/2	29	10	20	12	26	23	0.15	2
--	0.9	05B0320	05B0380	5/8	36	12	24	14	32	28	0.27	2
--	1.4	05B0330	05B0390	3/4	45	14	30	17	40	35	0.54	2
--	2	05B0340	05B0400	7/8	52	17	35	21	46	40	0.85	2
--	3.5	-	05B0420	1.1/8	65	22	44	26	58	51	1.62	2
--	4.5	-	05B0430	1.1/4	72	24	48	29	64	56	2.37	2
--	6.5	-	05B0440	1.1/2	86	29	57	33	76	67	3.81	2
--	9	-	-	1.3/4	101	34	68	40	90	79	6.27	2
--	12	-	-	2	115	38	76	46	102	89	9.58	2