



Porta-Gantry

Product information

4:1 strength to weight ratio, high tensile alloy compared with steel
 Rapid assembly – dismantles into 3 portable parts on 4 bolts
 Ease of transportation – of van or trailer
 Flat-packability – A-Frame legs fold-in for more compact transport or storage.
 Safety features
 Beam section has great torsional stability compared to I sections.
 Captive beam trolley is inherently safe.
 Trolley friction brake
 Ease of handling
 Simple height & span adjustment
 Castor wheels are 360° swivel locking with anti-scurf polyurethane tread
 Carry handles to beams.
 Finger grips on custom beam and leg sections.
 Anodised alloy surface finish as standard
 Suitable for clean environments.
 Corrosion resistant – low maintenance.
 Manual handling compliance – without mechanical aids

Features: Lightweight & Portable

Part Code	WLL	Min Height to lifting eye mm	Fully assembled weight kg	Beam weight kg	A-Frame weight	A mm	B mm	C mm	D mm	E mm	F mm	G mm	Weight kg
6015	500	1,611	66	16	25	2,500	200	1,580	2,361	150	2,678	1,220	16
6015	1,000	2,104	107	27	40	3,920	200	3,000	2,854	150	3,171	1,429	27
6015	2,000	2,143	136	33	52	4,570	200	3,650	3,143	200	3,459	1,726	33
6015	3,000	2,889	210	50	80	4,570	200	3,650	4,089	200	4,405	2,011	50

Blueprint

