

Polypropylene Fibre Rope 3-Strand.



Product information

Fibre rope of polypropylene for all different kinds of applications like: tarpaulin- and towing-ropes, lifting slings, ropes for the fishing industry, cargo nets, rope ladders, and more. The structure of the fibre rope makes it non-sliding in knots and splices.

Design: Spliced fibre.

Specific gravity: 0,91 (floats).

Melting point: Approx. 165°C.

Elongation at MBL: Approx. 30%.

Strength wet/dry: 100%

Shock Absorption: Very Good

Water Absorption: None

Abrasion Resistance: Good

Material: Polypropylene, resistant to rot, most acids and alkalies. The fibre is UV-stabilized against sunlight.

Marking: According to standard

Finish: Blue.

Standard: EN ISO 1346

Part code	Diameter mm	MBL	Length m	Circ. inches	Weight kg/220m
300300402200010	4	0.28	220	3	1.54
300300409990010	4	0.28	1,000	3	1.54
300300502200010	5	0.45	220	3 1/4	2.42
300300602200010	6	0.55	220	3 1/2	3.52
300300605000010	6	0.55	500	3 1/2	3.52
300300802200010	8	0.96	220	3 3/4	6.38
300300803110010	8	0.96	311	3 3/4	6.38
300301002080010	10	1.43	208	4	9.9
300301002200010	10	1.43	220	4	9.9
300301200500010	12	2.03	50	4 1/2	14.3
300301202200010	12	2.03	220	4 1/2	14.3
300301400300010	14	2.79	30	5	19.58
300301402200010	14	2.79	220	5	19.58
300301600300010	16	3.5	30	5 1/2	25.52
300301602200010	16	3.5	220	5 1/2	25.52
300301802200010	18	4.45	220	6	32.12
300302002200010	20	5.37	220	3	39.82
300302202200010	22	6.5	220	3 1/4	48.18
300302402200010	24	7.6	220	3	57.2
300302602200010	26	8.45	220	3 1/4	67.32
300302802200010	28	10.1	220	3 1/2	77.88
300303202200010	32	12.8	220	4	101.86
300303602200010	36	16.1	220	4 1/2	128.92