

## Chain sling 1-leg with swivel ball bearing safety hook, grade 8

### Product information



1-Leg chain sling assembly equipped with swivel ball bearing safety hook and grab hook. Alternative ends are also available, e.g. foundry hooks, shackles etc. Slings are equipped with a load plate.

... [Read more](#)

**Material:** Steel

**Marking:** According to standard, CE-marked

**Temperature range:** -40 °C up to +200°C

**Finish:** Painted, black / yellow

**Standard:** EN 818-4

**Warning:** Not to be heat-treated

**Safety factor:** 4:1

**Grade:** 8

## Chain sling 1-leg with swivel ball bearing safety hook, grade 8

### Technical data

| Part code       | Chain diameter<br>mm | WLL<br>ton | EWL<br>m | Weight<br>kg |
|-----------------|----------------------|------------|----------|--------------|
| 230500600100140 | 6                    | 1.12       | 1        | 3.71         |
| 230500600200140 | 6                    | 1.12       | 2        | 5.12         |
| 230500600300140 | 6                    | 1.12       | 3        | 6.54         |
| 230500600400140 | 6                    | 1.12       | 4        | 7.96         |
| 230500600500140 | 6                    | 1.12       | 5        | 9.38         |
| 230500600600140 | 6                    | 1.12       | 6        | 10.8         |
| 230500600700140 | 6                    | 1.12       | 7        | 12.22        |
| 230500600800140 | 6                    | 1.12       | 8        | 13.64        |
| 230500800100140 | 8                    | 2          | 1        | 3.71         |
| 230500800200140 | 8                    | 2          | 2        | 5.12         |
| 230500800300140 | 8                    | 2          | 3        | 6.54         |
| 230500800400140 | 8                    | 2          | 4        | 7.96         |
| 230500800500140 | 8                    | 2          | 5        | 9.38         |
| 230500800600140 | 8                    | 2          | 6        | 10.8         |
| 230500800700140 | 8                    | 2          | 7        | 12.22        |
| 230500800800140 | 8                    | 2          | 8        | 13.64        |
| 230501000100140 | 10                   | 3.15       | 1        | 6.29         |
| 230501000200140 | 10                   | 3.15       | 2        | 8.5          |
| 230501000300140 | 10                   | 3.15       | 3        | 10.72        |
| 230501000400140 | 10                   | 3.15       | 4        | 12.94        |
| 230501000500140 | 10                   | 3.15       | 5        | 15.16        |
| 230501000600140 | 10                   | 3.15       | 6        | 17.38        |
| 230501000700140 | 10                   | 3.15       | 7        | 19.6         |
| 230501000800140 | 10                   | 3.15       | 8        | 21.82        |
| 230501300100140 | 13                   | 5.3        | 1        | 11.5         |
| 230501300200140 | 13                   | 5.3        | 2        | 15.25        |
| 230501300300140 | 13                   | 5.3        | 3        | 19           |
| 230501300400140 | 13                   | 5.3        | 4        | 22.75        |
| 230501300500140 | 13                   | 5.3        | 5        | 26.5         |
| 230501300600140 | 13                   | 5.3        | 6        | 30.25        |
| 230501300700140 | 13                   | 5.3        | 7        | 34           |

## Chain sling 1-leg with swivel ball bearing safety hook, grade 8

### Technical data

| Part code       | Chain diameter<br>mm | WLL<br>ton | EWL<br>m | Weight<br>kg |
|-----------------|----------------------|------------|----------|--------------|
| 230501300800140 | 13                   | 5.3        | 8        | 37.75        |
| 230501600100140 | 16                   | 8          | 1        | 19.01        |
| 230501600200140 | 16                   | 8          | 2        | 24.58        |
| 230501600300140 | 16                   | 8          | 3        | 30.15        |
| 230501600400140 | 16                   | 8          | 4        | 35.72        |
| 230501600500140 | 16                   | 8          | 5        | 41.29        |
| 230501600600140 | 16                   | 8          | 6        | 46.86        |
| 230501600700140 | 16                   | 8          | 7        | 52.43        |
| 230501600800140 | 16                   | 8          | 8        | 58           |
| 230502000200140 | 20                   | 12.5       | 2        | 37.4         |
| 230502000300140 | 20                   | 12.5       | 3        | 46.5         |
| 230502000400140 | 20                   | 12.5       | 4        | 55.6         |
| 230502000500140 | 20                   | 12.5       | 5        | 64.7         |
| 230502000600140 | 20                   | 12.5       | 6        | 73.8         |
| 230502000700140 | 20                   | 12.5       | 7        | 82.9         |
| 230502000800140 | 20                   | 12.5       | 8        | 92           |
| 230502200200140 | 22                   | 15         | 2        | 55.4         |
| 230502200300140 | 22                   | 15         | 3        | 66.4         |
| 230502200400140 | 22                   | 15         | 4        | 77.4         |
| 230502200500140 | 22                   | 15         | 5        | 88.4         |
| 230502200600140 | 22                   | 15         | 6        | 99.4         |
| 230502200700140 | 22                   | 15         | 7        | 110.4        |
| 230502200800140 | 22                   | 15         | 8        | 121.4        |
| 230502600200140 | 26                   | 21.2       | 2        | 74.2         |
| 230502600300140 | 26                   | 21.2       | 3        | 89.5         |
| 230502600400140 | 26                   | 21.2       | 4        | 104.8        |
| 230502600500140 | 26                   | 21.2       | 5        | 120.1        |
| 230502600600140 | 26                   | 21.2       | 6        | 135.4        |
| 230502600700140 | 26                   | 21.2       | 7        | 150.7        |
| 230502600800140 | 26                   | 21.2       | 8        | 166          |