



Chain sling 1-leg with safety hook, grade 8

Product information

1-Leg chain sling assembly equipped with safety hook and grab hook. Alternative ends are also available, e.g. foundry hooks, shackles etc. Slings are equipped with a load plate.

Material: Steel

Marking: According to standard, CE-marked

Temperature range: -40 °C up to +200°C

Finish: Painted, black / yellow

Standard: EN 818-4

Warning: Not to be heat-treated

Safety factor: 4:1

Grade: 8

Part code	Chain diameter mm	WLL ton	EWL m	Weight kg
230500600100130	6	1.12	1	3.36
230500600200130	6	1.12	2	4.77
230500600300130	6	1.12	3	6.19
230500600400130	6	1.12	4	7.61
230500600500130	6	1.12	5	9.03
230500600600130	6	1.12	6	10.45
230500600700130	6	1.12	7	11.87
230500600800130	6	1.12	8	13.29
230500800100130	8	2	1	3.36
230500800200130	8	2	2	4.77

230500800300130	8	2	3	6.19
230500800400130	8	2	4	7.61
230500800500130	8	2	5	9.03
230500800600130	8	2	6	10.45
230500800700130	8	2	7	11.87
230500800800130	8	2	8	13.29
230501000100130	10	3.15	1	5.58
230501000200130	10	3.15	2	7.79
230501000300130	10	3.15	3	10.01
230501000400130	10	3.15	4	12.23
230501000500130	10	3.15	5	14.45
230501000600130	10	3.15	6	16.67
230501000700130	10	3.15	7	18.89
230501000800130	10	3.15	8	21.11
230501300100130	13	5.3	1	10.62
230501300200130	13	5.3	2	14.37
230501300300130	13	5.3	3	18.12
230501300400130	13	5.3	4	21.87
230501300500130	13	5.3	5	25.62
230501300600130	13	5.3	6	29.37
230501300700130	13	5.3	7	33.12
230501300800130	13	5.3	8	36.87
230501600100130	16	8	1	17.51
230501600200130	16	8	2	23.08
230501600300130	16	8	3	28.65
230501600400130	16	8	4	34.22

230501600500130	16	8	5	39.79
230501600600130	16	8	6	45.36
230501600700130	16	8	7	50.93
230501600800130	16	8	8	56.5
230502000200130	20	12.5	2	37.4
230502000300130	20	12.5	3	46.5
230502000400130	20	12.5	4	55.6
230502000500130	20	12.5	5	64.7
230502000600130	20	12.5	6	73.8
230502000700130	20	12.5	7	82.9
230502000800130	20	12.5	8	92
230502200200130	22	15	2	55.4
230502200300130	22	15	3	66.4
230502200400130	22	15	4	77.4
230502200500130	22	15	5	88.4
230502200600130	22	15	6	99.4
230502200700130	22	15	7	110.4
230502200800130	22	15	8	121.4
230502600200130	26	21.2	2	74.2
230502600300130	26	21.2	3	89.5
230502600400130	26	21.2	4	104.8
230502600500130	26	21.2	5	120.1
230502600600130	26	21.2	6	135.4
230502600700130	26	21.2	7	150.7
230502600800130	26	21.2	8	166