

Chain sling 2-leg with safety hook, grade 8

Product information



2-legs chain sling assembly equipped with safety hooks and grab hooks. Alternative ends are also available, e.g. foundry hooks, shackles etc. Slings are equipped with a load plate.

... [Read more](#)

Material: Steel

Marking: According to standard, CE-marked

Temperature range: -40 °C up to +200°C

Finish: Painted, black / yellow

Standard: EN 818-4

Warning: Not to be heat-treated

Safety factor: 4:1

Grade: 8

Chain sling 2-leg with safety hook, grade 8

Technical data

| Part code | Chain diameter mm | WLL ton | EWL m | Weight kg |
|-----------------|----------------------|------------|----------|--------------|
| 230800600100130 | 6 | 1.6 | 1 | 6.45 |
| 230800600200130 | 6 | 1.6 | 2 | 9.28 |
| 230800600300130 | 6 | 1.6 | 3 | 12.11 |
| 230800600400130 | 6 | 1.6 | 4 | 14.94 |
| 230800600500130 | 6 | 1.6 | 5 | 17.77 |
| 230800600600130 | 6 | 1.6 | 6 | 20.6 |
| 230800600700130 | 6 | 1.6 | 7 | 23.43 |
| 230800600800130 | 6 | 1.6 | 8 | 26.26 |
| 230800800100130 | 8 | 2.8 | 1 | 6.45 |
| 230800800200130 | 8 | 2.8 | 2 | 9.28 |
| 230800800300130 | 8 | 2.8 | 3 | 12.11 |
| 230800800400130 | 8 | 2.8 | 4 | 14.94 |
| 230800800500130 | 8 | 2.8 | 5 | 17.77 |
| 230800800600130 | 8 | 2.8 | 6 | 20.6 |
| 230800800700130 | 8 | 2.8 | 7 | 23.43 |
| 230800800800130 | 8 | 2.8 | 8 | 26.26 |
| 230801000100130 | 10 | 4.25 | 1 | 11.01 |
| 230801000200130 | 10 | 4.25 | 2 | 15.44 |
| 230801000300130 | 10 | 4.25 | 3 | 19.88 |
| 230801000400130 | 10 | 4.25 | 4 | 24.31 |
| 230801000500130 | 10 | 4.25 | 5 | 28.74 |
| 230801000600130 | 10 | 4.25 | 6 | 33.17 |
| 230801000700130 | 10 | 4.25 | 7 | 37.6 |
| 230801000800130 | 10 | 4.25 | 8 | 42.03 |
| 230801300100130 | 13 | 7.5 | 1 | 20.56 |
| 230801300200130 | 13 | 7.5 | 2 | 28.06 |
| 230801300300130 | 13 | 7.5 | 3 | 35.56 |
| 230801300400130 | 13 | 7.5 | 4 | 43.06 |
| 230801300500130 | 13 | 7.5 | 5 | 50.56 |
| 230801300600130 | 13 | 7.5 | 6 | 58.06 |
| 230801300700130 | 13 | 7.5 | 7 | 65.56 |

Chain sling 2-leg with safety hook, grade 8

Technical data

| Part code | Chain diameter mm | WLL ton | EWL m | Weight kg |
|-----------------|----------------------|------------|----------|--------------|
| 230801300800130 | 13 | 7.5 | 8 | 73.06 |
| 230801600200130 | 16 | 11.2 | 2 | 45.32 |
| 230801600300130 | 16 | 11.2 | 3 | 56.46 |
| 230801600400130 | 16 | 11.2 | 4 | 67.6 |
| 230801600500130 | 16 | 11.2 | 5 | 78.74 |
| 230801600600130 | 16 | 11.2 | 6 | 89.88 |
| 230801600700130 | 16 | 11.2 | 7 | 101.02 |
| 230801600800130 | 16 | 11.2 | 8 | 112.16 |
| 230802000200130 | 20 | 17 | 2 | 70.1 |
| 230802000300130 | 20 | 17 | 3 | 88.3 |
| 230802000400130 | 20 | 17 | 4 | 106.5 |
| 230802000500130 | 20 | 17 | 5 | 124.7 |
| 230802000600130 | 20 | 17 | 6 | 142.9 |
| 230802000700130 | 20 | 17 | 7 | 161.1 |
| 230802000800130 | 20 | 17 | 8 | 179.3 |
| 230802200200130 | 22 | 21.2 | 2 | 105.7 |
| 230802200300130 | 22 | 21.2 | 3 | 127.7 |
| 230802200400130 | 22 | 21.2 | 4 | 149.7 |
| 230802200500130 | 22 | 21.2 | 5 | 171.7 |
| 230802200600130 | 22 | 21.2 | 6 | 193.7 |
| 230802200700130 | 22 | 21.2 | 7 | 215.7 |
| 230802200800130 | 22 | 21.2 | 8 | 237.7 |
| 230802600200130 | 26 | 30 | 2 | 141.4 |
| 230802600300130 | 26 | 30 | 3 | 172 |
| 230802600400130 | 26 | 30 | 4 | 202.6 |
| 230802600500130 | 26 | 30 | 5 | 233.2 |
| 230802600600130 | 26 | 30 | 6 | 263.8 |
| 230802600700130 | 26 | 30 | 7 | 294.4 |
| 230802600800130 | 26 | 30 | 8 | 325 |