

Chain sling 1-leg with latch hook, grade 10



Product information

1-Leg chain sling assembly equipped with latch hook and grab hook. Alternative ends are also available, e.g. foundry hooks, shackles etc. Slings are equipped with a load plate.

Material: Steel

Marking: CE-marked

Temperature range: -40 °C up to +200°C

Finish: Painted

Warning: Not to be heat-treated

Safety factor: 4:1

Grade: 10

Part code	Chain diameter mm	WLL ton	EWL m
240500600100190	6	1.4	1
240500600200190	6	1.4	2
240500600300190	6	1.4	3
240500600400190	6	1.4	4
240500600500190	6	1.4	5
240500600600190	6	1.4	6
240500600700190	6	1.4	7
240500600800190	6	1.4	8

240500800100190	8	2.5	1
240500800200190	8	2.5	2
240500800300190	8	2.5	3
240500800400190	8	2.5	4
240500800500190	8	2.5	5
240500800600190	8	2.5	6
240500800700190	8	2.5	7
240500800800190	8	2.5	8
240501000100190	10	4	1
240501000200190	10	4	2
240501000300190	10	4	3
240501000400190	10	4	4
240501000500190	10	4	5
240501000600190	10	4	6
240501000700190	10	4	7
240501000800190	10	4	8
240501300100190	13	6.7	1
240501300200190	13	6.7	2
240501300300190	13	6.7	3
240501300400190	13	6.7	4
240501300500190	13	6.7	5
240501300600190	13	6.7	6
240501300700190	13	6.7	7

240501300800190	13	6.7	8
240501600100190	16	10	1
240501600200190	16	10	2
240501600300190	16	10	3
240501600400190	16	10	4
240501600500190	16	10	5
240501600600190	16	10	6
240501600700190	16	10	7
240501600800190	16	10	8
240502000200190	20	16	2
240502000300190	20	16	3
240502000400190	20	16	4
240502000500190	20	16	5
240502000600190	20	16	6
240502000700190	20	16	7
240502000800190	20	16	8
240502200200190	22	19	2
240502200300190	22	19	3
240502200400190	22	19	4
240502200500190	22	19	5
240502200600190	22	19	6
240502200700190	22	19	7
240502200800190	22	19	8

240502600200190	26	26.5	2
240502600300190	26	26.5	3
240502600400190	26	26.5	4
240502600500190	26	26.5	5
240502600600190	26	26.5	6
240502600700190	26	26.5	7
240502600800190	26	26.5	8