

Chain sling 1-leg with safety hook, grade 10



Product information

1-Leg chain sling assembly equipped with safety hook and grab hook. Alternative ends are also available, e.g. foundry hooks, shackles etc. Slings are equipped with a load plate.

Material: Steel

Marking: CE-marked

Temperature range: -40 °C up to +200°C

Finish: Painted

Warning: Not to be heat-treated

Safety factor: 4:1

Grade: 10

Part code	Chain diameter mm	WLL ton	EWL m
240500600100210	6	1.4	1
240500600200210	6	1.4	2
240500600300210	6	1.4	3
240500600400210	6	1.4	4
240500600500210	6	1.4	5
240500600600210	6	1.4	6
240500600700210	6	1.4	7
240500600800210	6	1.4	8

240500800100210	8	2.5	1
240500800200210	8	2.5	2
240500800300210	8	2.5	3
240500800400210	8	2.5	4
240500800500210	8	2.5	5
240500800600210	8	2.5	6
240500800700210	8	2.5	7
240500800800210	8	2.5	8
240501000100210	10	4	1
240501000200210	10	4	2
240501000300210	10	4	3
240501000400210	10	4	4
240501000500210	10	4	5
240501000600210	10	4	6
240501000700210	10	4	7
240501000800210	10	4	8
240501300100210	13	6.7	1
240501300200210	13	6.7	2
240501300300210	13	6.7	3
240501300400210	13	6.7	4
240501300500210	13	6.7	5
240501300600210	13	6.7	6
240501300700210	13	6.7	7

240501300800210	13	6.7	8
240501600100210	16	10	1
240501600200210	16	10	2
240501600300210	16	10	3
240501600400210	16	10	4
240501600500210	16	10	5
240501600600210	16	10	6
240501600700210	16	10	7
240501600800210	16	10	8
240502000200210	20	16	2
240502000300210	20	16	3
240502000400210	20	16	4
240502000500210	20	16	5
240502000600210	20	16	6
240502000700210	20	16	7
240502000800210	20	16	8
240502200200210	22	19	2
240502200300210	22	19	3
240502200400210	22	19	4
240502200500210	22	19	5
240502200600210	22	19	6
240502200700210	22	19	7
240502200800210	22	19	8

240502600200210	26	26.5	2
240502600300210	26	26.5	3
240502600400210	26	26.5	4
240502600500210	26	26.5	5
240502600600210	26	26.5	6
240502600700210	26	26.5	7
240502600800210	26	26.5	8