



Chain sling 1-leg with swivel ball bearing safety hook, grade 10

Product information

1-Leg chain sling assembly equipped with swivel ball bearing hook and grab hook. Alternative ends are also available, e.g. foundry hooks, shackles etc. Slings are equipped with a load plate.

Material: Steel

Marking: CE-marked

Temperature range: -40 °C up to +200°C

Finish: Painted

Warning: Not to be heat-treated

Safety factor: 4:1

Grade: 10

Part code	Chain diameter mm	WLL ton	EWL m
240500600100230	6	1.4	1
240500600200230	6	1.4	2
240500600300230	6	1.4	3
240500600400230	6	1.4	4
240500600500230	6	1.4	5
240500600600230	6	1.4	6
240500600700230	6	1.4	7
240500600800230	6	1.4	8

240500800100230	8	2.5	1
240500800200230	8	2.5	2
240500800300230	8	2.5	3
240500800400230	8	2.5	4
240500800500230	8	2.5	5
240500800600230	8	2.5	6
240500800700230	8	2.5	7
240500800800230	8	2.5	8
240501000100230	10	4	1
240501000200230	10	4	2
240501000300230	10	4	3
240501000400230	10	4	4
240501000500230	10	4	5
240501000600230	10	4	6
240501000700230	10	4	7
240501000800230	10	4	8
240501300100230	13	6.7	1
240501300200230	13	6.7	2
240501300300230	13	6.7	3
240501300400230	13	6.7	4
240501300500230	13	6.7	5
240501300600230	13	6.7	6
240501300700230	13	6.7	7

240501300800230	13	6.7	8
240501600100230	16	10	1
240501600200230	16	10	2
240501600300230	16	10	3
240501600400230	16	10	4
240501600500230	16	10	5
240501600600230	16	10	6
240501600700230	16	10	7
240501600800230	16	10	8
240502000200230	20	16	2
240502000300230	20	16	3
240502000400230	20	16	4
240502000500230	20	16	5
240502000600230	20	16	6
240502000700230	20	16	7
240502000800230	20	16	8
240502200200230	22	19	2
240502200300230	22	19	3
240502200400230	22	19	4
240502200500230	22	19	5
240502200600230	22	19	6
240502200700230	22	19	7
240502200800230	22	19	8

240502600200230	26	26.5	2
240502600300230	26	26.5	3
240502600400230	26	26.5	4
240502600500230	26	26.5	5
240502600600230	26	26.5	6
240502600700230	26	26.5	7
240502600800230	26	26.5	8