

Chain sling 2-leg with latch hook, grade 10



Product information

2-Leg chain sling assembly equipped with latch hooks and grab hooks. Alternative ends are also available, e.g. foundry hooks, shackles etc. Slings are equipped with a load plate.

Material: Steel

Marking: CE-marked

Temperature range: -40 °C up to +200°C

Finish: Painted

Warning: Not to be heat-treated

Safety factor: 4:1

Grade: 10

Part code	Chain diameter mm	WLL ton	EWL m
240800600100180	6	2	1
240800600200180	6	2	2
240800600300180	6	2	3
240800600400180	6	2	4
240800600500180	6	2	5
240800600600180	6	2	6
240800600700180	6	2	7
240800600800180	6	2	8

240800800100180	8	3.55	1
240800800200180	8	3.55	2
240800800300180	8	3.55	3
240800800400180	8	3.55	4
240800800500180	8	3.55	5
240800800600180	8	3.55	6
240800800700180	8	3.55	7
240800800800180	8	3.55	8
240801000100180	10	5.6	1
240801000200180	10	5.6	2
240801000300180	10	5.6	3
240801000400180	10	5.6	4
240801000500180	10	5.6	5
240801000600180	10	5.6	6
240801000700180	10	5.6	7
240801000800180	10	5.6	8
240801300100180	13	9.5	1
240801300200180	13	9.5	2
240801300300180	13	9.5	3
240801300400180	13	9.5	4
240801300500180	13	9.5	5
240801300600180	13	9.5	6
240801300700180	13	9.5	7

240801300800180	13	9.5	8
240801600200180	16	14	2
240801600300180	16	14	3
240801600400180	16	14	4
240801600500180	16	14	5
240801600600180	16	14	6
240801600700180	16	14	7
240801600800180	16	14	8
240802000200180	20	22.4	2
240802000300180	20	22.4	3
240802000400180	20	22.4	4
240802000500180	20	22.4	5
240802000600180	20	22.4	6
240802000700180	20	22.4	7
240802000800180	20	22.4	8
240802200200180	22	26.5	2
240802200300180	22	26.5	3
240802200400180	22	26.5	4
240802200500180	22	26.5	5
240802200600180	22	26.5	6
240802200700180	22	26.5	7
240802200800180	22	26.5	8
240802600200180	26	37.5	2

240802600300180	26	37.5	3
240802600400180	26	37.5	4
240802600500180	26	37.5	5
240802600600180	26	37.5	6
240802600700180	26	37.5	7
240802600800180	26	37.5	8