

Chain sling 2-leg with safety hook, grade 10



Product information

2-Leg chain sling assembly equipped with safety hooks and grab hooks. Alternative ends are also available, e.g. foundry hooks, shackles etc. Slings are equipped with a load plate.

Material: Steel

Marking: CE-marked

Temperature range: -40 °C up to +200°C

Finish: Painted

Warning: Not to be heat-treated

Safety factor: 4:1

Grade: 10

Part code	Chain diameter mm	WLL ton	EWL m
240800600100160	6	2	1
240800600200160	6	2	2
240800600300160	6	2	3
240800600400160	6	2	4
240800600500160	6	2	5
240800600600160	6	2	6
240800600700160	6	2	7
240800600800160	6	2	8

240800800100160	8	3.5	1
240800800200160	8	3.5	2
240800800300160	8	3.5	3
240800800400160	8	3.5	4
240800800500160	8	3.5	5
240800800600160	8	3.5	6
240800800700160	8	3.5	7
240800800800160	8	3.5	8
240801000100160	10	5.6	1
240801000200160	10	5.6	2
240801000300160	10	5.6	3
240801000400160	10	5.6	4
240801000500160	10	5.6	5
240801000600160	10	5.6	6
240801000700160	10	5.6	7
240801000800160	10	5.6	8
240801300100160	13	9.5	1
240801300200160	13	9.5	2
240801300300160	13	9.5	3
240801300400160	13	9.5	4
240801300500160	13	9.5	5
240801300600160	13	9.5	6
240801300700160	13	9.5	7

240801300800160	13	9.5	8
240801600100160	16	14	1
240801600200160	16	14	2
240801600300160	16	14	3
240801600400160	16	14	4
240801600500160	16	14	5
240801600600160	16	14	6
240801600700160	16	14	7
240801600800160	16	14	8
240802000200160	20	22.4	2
240802000300160	20	22.4	3
240802000400160	20	22.4	4
240802000500160	20	22.4	5
240802000600160	20	22.4	6
240802000700160	20	22.4	7
240802000800160	20	22.4	8
240802200200160	22	26.5	2
240802200300160	22	26.5	3
240802200400160	22	26.5	4
240802200500160	22	26.5	5
240802200600160	22	26.5	6
240802200700160	22	26.5	7
240802200800160	22	26.5	8

240802600200160	26	37.1	2
240802600300160	26	37.1	3
240802600400160	26	37.1	4
240802600500160	26	37.1	5
240802600600160	26	37.1	6
240802600700160	26	37.1	7
240802600800160	26	37.1	8