



Chain sling 4-leg with latch hook, grade 10

Product information

4-Leg chain sling assembly equipped with latch hooks and grab hooks. Alternative ends are also available, e.g. foundry hooks, shackles etc. Slings are equipped with a load plate.

Material: Steel

Marking: CE-marked

Temperature range: -40 °C up to +200°C

Finish: Painted

Warning: Not to be heat-treated

Safety factor: 4:1

Grade: 10

Part code	Chain diameter mm	WLL ton	EWL m
241300600100200	6	3	1
241300600200200	6	3	2
241300600300200	6	3	3
241300600400200	6	3	4
241300600500200	6	3	5
241300600600200	6	3	6
241300600700200	6	3	7
241300600800200	6	3	8

241300800100200	8	5.3	1
241300800200200	8	5.3	2
241300800300200	8	5.3	3
241300800400200	8	5.3	4
241300800500200	8	5.3	5
241300800600200	8	5.3	6
241300800700200	8	5.3	7
241300800800200	8	5.3	8
241301000100200	10	8.4	1
241301000200200	10	8.4	2
241301000300200	10	8.4	3
241301000400200	10	8.4	4
241301000500200	10	8.4	5
241301000600200	10	8.4	6
241301000700200	10	8.4	7
241301000800200	10	8.4	8
241301300200200	13	14	2
241301300300200	13	14	3
241301300400200	13	14	4
241301300500200	13	14	5
241301300600200	13	14	6
241301300700200	13	14	7
241301300800200	13	14	8

241301600200200	16	21.2	2
241301600300200	16	21.2	3
241301600400200	16	21.2	4
241301600500200	16	21.2	5
241301600600200	16	21.2	6
241301600700200	16	21.2	7
241301600800200	16	21.2	8
241302000200200	20	33.6	2
241302000300200	20	33.6	3
241302000400200	20	33.6	4
241302000500200	20	33.6	5
241302000600200	20	33.6	6
241302000700200	20	33.6	7
241302000800200	20	33.6	8
241302200200200	22	40	2
241302200300200	22	40	3
241302200400200	22	40	4
241302200500200	22	40	5
241302200600200	22	40	6
241302200700200	22	40	7
241302200800200	22	40	8
241302600200200	26	56	2
241302600300200	26	56	3

241302600400200	26	56	4
241302600500200	26	56	5
241302600600200	26	56	6
241302600700200	26	56	7
241302600800200	26	56	8