



Chain sling 4-leg with safety hook, grade 10

Product information

4-Leg chain sling assembly equipped with safety hooks and grab hooks. Alternative ends are also available, e.g. foundry hooks, shackles etc. Slings are equipped with a load plate.

Material: Steel

Marking: CE-marked

Temperature range: -29 - (+)205°C

Finish: Painted

Warning: Not to be heat-treated

Safety factor: 4:1

Grade: 10

Part code	Chain diameter mm	WLL ton	EWL m
241300600100180	6	3	1
241300600200180	6	3	2
241300600300180	6	3	3
241300600400180	6	3	4
241300600500180	6	3	5
241300600600180	6	3	6
241300600700180	6	3	7
241300600800180	6	3	8

241300800100180	8	5.3	1
241300800200180	8	5.3	2
241300800300180	8	5.3	3
241300800400180	8	5.3	4
241300800500180	8	5.3	5
241300800600180	8	5.3	6
241300800700180	8	5.3	7
241300800800180	8	5.3	8
241301000100180	10	8.4	1
241301000200180	10	8.4	2
241301000300180	10	8.4	3
241301000400180	10	8.4	4
241301000500180	10	8.4	5
241301000600180	10	8.4	6
241301000700180	10	8.4	7
241301000800180	10	8.4	8
241301300200180	13	14	2
241301300300180	13	14	3
241301300400180	13	14	4
241301300500180	13	14	5
241301300600180	13	14	6
241301300700180	13	14	7
241301300800180	13	14	8

241301600200180	16	21.2	2
241301600300180	16	21.2	3
241301600400180	16	21.2	4
241301600500180	16	21.2	5
241301600600180	16	21.2	6
241301600700180	16	21.2	7
241301600800180	16	21.2	8
241302000200180	20	33.6	2
241302000300180	20	33.6	3
241302000400180	20	33.6	4
241302000500180	20	33.6	5
241302000600180	20	33.6	6
241302000700180	20	33.6	7
241302000800180	20	33.6	8
241302200200180	22	40	2
241302200300180	22	40	3
241302200400180	22	40	4
241302200500180	22	40	5
241302200600180	22	40	6
241302200700180	22	40	7
241302200800180	22	40	8
241302600200180	26	56	2
241302600300180	26	56	3

241302600400180	26	56	4
241302600500180	26	56	5
241302600600180	26	56	6
241302600700180	26	56	7
241302600800180	26	56	8