



Dee Shackles with Screw Collar Pin Yellow Pin G-3151

Product information

Dee shackle with screw collar pin.

Certification on request: 2.1, 2.2

Standard: Generally to US Fed. Spec. RR-C-271.

Material: Bow and pin high tensile steel

Marking: CE-marked

Finish: Hot dipped galvanized

Note: Import quality

Safety factor: 5:1

Grade: 6

| Part code | Diameter mm | WLL ton | Size | a mm | b mm | c mm | d mm | e mm | Weight kg |
|------------------|------------------------|--------------------|-------------|-----------------|-----------------|-----------------|-----------------|-----------------|----------------------|
| 420100030490 | 12 | 0.33 | 19 | 5 | 6 | 12 | 9.5 | 19 | 0.03 |
| 420100050490 | 16 | 0.5 | 22 | 6 | 8 | 16 | 12 | 22 | 0.04 |
| 420100080490 | 19 | 0.75 | 26 | 8 | 10 | 19 | 13.5 | 26 | 0.08 |
| 420100100490 | 23 | 1 | 32 | 10 | 11 | 23 | 17 | 32 | 0.13 |
| 420100150490 | 27 | 1.5 | 37 | 11 | 13 | 27 | 19 | 37 | 0.2 |
| 420100200490 | 30 | 2 | 41 | 13 | 16 | 30 | 20 | 41 | 0.28 |
| 420100330490 | 38 | 3.25 | 51 | 16 | 19 | 38 | 27 | 51 | 0.57 |
| 420100480490 | 46 | 4.75 | 60 | 19 | 22 | 46 | 32 | 60 | 1.19 |
| 420100650490 | 53 | 6.5 | 71 | 22 | 25 | 53 | 36 | 71 | 1.43 |
| 420100850490 | 61 | 8.5 | 81 | 25 | 28 | 61 | 43 | 81 | 2.16 |
| 420100950490 | 68 | 9.5 | 90 | 28 | 32 | 68 | 46 | 90 | 3.06 |
| 420101200490 | 76 | 12 | 100 | 32 | 35 | 76 | 51 | 100 | 4.11 |
| 420101350490 | 84 | 13.5 | 111 | 35 | 38 | 84 | 57 | 111 | 5.28 |
| 420101700490 | 92 | 17 | 122 | 38 | 42 | 92 | 60 | 122 | 6.69 |
| 420102500490 | 106 | 25 | 146 | 45 | 50 | 106 | 73 | 146 | 12.14 |

Blueprint

