

Female Swivel eye bolt Codipro FE SEB UP

Product information



The SEB lifting eye nut is a single swivel ring. Equipped with 2 pins that always guide it perfectly in the direction of the sling. It is specially designed for lifting, including rotating loads.

Features:

- Gradup steel ring that has a rotating range of 360°.
- Swivelling under load.
- Safe alternative to C15 DIN 580 eye nuts.
- Torque key adaptor available on request.

[... Read more](#)

Material: High tensile steel

Marking: According to standard, CE-marked

Temperature range: -20°C up to +200°C


Standard: EN 1677-1

except grade/WLL

Safety factor: 5:1

Female Swivel eye bolt Codipro FE SEB UP

Blueprint



Technical data

Part code	WLL ton	Thread	Torque Nm	A mm	B mm	C mm	D mm	L max. mm	Weight kg
4215FESEBM8UP	0.4	M 8 (x1,25)	6	38	45	88	80	22	0.8
4215FESEBM10UP	0.5	M 10 (x1,50)	10	38	45	88	80	22	0.8
4215FESEBM12UP	0.8	M 12 (x1,75)	15	38	45	88	80	22	0.8
4215FESEBM16UP	1.4	M 16 (x2)	50	38	45	88	80	22	0.8
4215FESEBM20UP	2	M 20 (x2,5)	100	55	70	115	106	35	2.5
4215FESEBM24UP	3.4	M 24 (x3)	160	77	94	168	155	48	6.3
4215FESEBM30UP	5.5	M 30 (x3,5)	250	77	94	168	155	48	6.3
4215FESEBM36UP	9	M 36 (x4)	320	77	94	168	155	48	6.3