

Double Swivel Ring Codipro OS DSR UP UNC



Product information

Standard metric and UNC threads available

M 5 to M 42

WLL 0.07 ton to 9.00 ton

UNC 1/4" to UNC 1" 1/4

WLL 330 lbs to 13,500 lbs

- Swing under load 360° rotation - 180° swing.
- Complies with Machinery Directive 2006/42/CE.
- Produced in accordance with the EN 1677-1 standard.
- Safety factor 4:1 and 5:1.

Marking: CE-marked, Individual marking

Safety factor: 5:1

Part code	WLL ton	Thread Inch	Torque Nm	A,	B,	C,	D,	E,	F,	G,	H,	L1 mm	S1 mm	S2 mm	Weight kg
4215OSDSRU050UP	0.6	UNC 3/8"-16	8	32	30	30	38	27	14	53	9.5	17	8	16	0.3
4215OSDSRU038UP	1.1	UNC 1/2"-13	12	32	30	30	38	27	14	53	9.5	21	8	16	0.3
4215OSDSRU058UP	1.8	UNC 5/8"-11	40	45	40	45	53	38	17	76	13	27	8	20	0.9
4215OSDSRU075UP	2.4	UNC 3/4"-10	80	45	40	45	53	38	17	76	13	30	8	20	0.9
4215OSDSRU100UP	5	UNC 1"-8	125	62	55	60	83	55	25	115	19	36	14	24	2.6
4215OSDSRU125UP	6.1	UNC 1" 1/4-7	200	62	55	60	83	55	25	115	19	45	14	24	2.7

Technical data

Blueprint

