

Fixed Jaw Super Clamp WH BC

Product information




The WH BC fixed jaw super clamp is fitted with a 'gussett' in both jaws maximising contact between the beam and clamp thus increasing the grip. A shackle is fitted to the bottom allowing an easy connection of the hoist to be attached. This fixed jaw super clamp can be used to an angle of 45° to the vertical. When the angle is moved away from the vertical the working load limit of the beam clamp needs to be reduced. Please refer to the table opposite – reduction in working load limits when side loads are applied.

... [Read more](#)

Fixed Jaw Super Clamp WH BC

Blueprint



Technical data

Part code	WLL ton	Beam width mm	A mm	B mm	D mm	E max mm mm	E min mm mm	G mm	K max mm	K minmm mm	H mm	Weight kg
502300201900790	2	76-190	130	3	90	254	133	275	263	223	20	4
502300321900790	3.2	76-190	130	12	102	275	166	275	289	251	20	8
502300323500790	3.2	127-350	130	12	102	438	228	560	375	294	20	11.5
502300402540790	4	150-254	130	10	112	371	185	410	369	308	25	11
502300501900790	5	76-190	130	12	116	306	191	295	338	300	25	10
502300503050790	5	150-305	130	12	116	422	264	410	413	360	25	15
502300604570790	6	203-457	140	12	116	608	267	560	511	402	25	18.8
502301004570790	10	203-457	140	20	118	608	267	560	530	421	32	28
502301504570790	15	203-457	170	20	116.5	648	400	660	684	608	40	49.5
502301506100790	15	406-610	170	20	116.5	800	600	810	812	706	40	58.5