Lifting Solutions Group
Axel Johnson International

Geared Trolley WH-GT

Product information



The William Hackett WH GT Geared Travel Trolleys range is precision engineered in capacities from 500kg to 10 tonne. Enabling exact positioning or easy traversing of large loads incorporating Manual hoists, the Hackett series push trolley can be supplied to suit various track widths with Beam Range 1 and the extended Beam Range 2. It has been designed so that the bottom of the hand chain loop is 500mm from ground level. The runners (trolley wheels) are precision machined and they rotate on maintenance sealed ball bearings. All Hackett geared trolleys are fitted with anti-jump bars and rubber end stops as standard.

... *Read more*


Marking: According to standard
Standard: EN 13157

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Geared Trolley WH-GT

Blueprint



Technical data

Part code	WLL ton	Beam width mm	Hand chain length m	a mm	b mm	c mm	e mm	Weight kg
502500052030610	0.5	50-203	3	190	154	22	27	9.6
502500103050610	1	64-305	3	206	180	30	26	12.3
502500102030610	1	64-203	3	206	180	30	26	12.3
502500203050610	2	88-305	3	246	210	37	26	17.2
502500202030610	2	88-203	3	246	210	37	26	17.2
502500323050610	3.2	100-305	3	300	249	42	28	28.4
502500322030610	3.2	100-203	3	300	249	42	28	28.4
502500503050610	5	114-305	3	336	277	50	37	40.1
502500502030610	5	114-203	3	336	277	50	37	40.1
502501003050610	10	124-305	3	396	334	58	37	62
502501002030610	10	124-203	3	396	334	58	37	62

© November 2026 - All Rights Reserved