

Push Trolley WH PT

Product information

The William Hackett WH PT Push Trolleys range is precision engineered in WLL capacities from 500kg to 10 tonnes. Enabling exact positioning or easy traversing of large loads incorporating manual hoists, the William Hackett series push trolley can be supplied to suit various track widths within the standard beam range 1 and the extended beam range 2. The runners (trolley wheels) are precision machined and they rotate on maintenance sealed ball bearings. All William Hackett push trolleys are fitted with anti-jump bars and rubber end stops as standard.

Marking: According to standard

Standard: EN 13157



Part code	WLL ton	Beam width mm	a mm	b mm	c mm	e mm	Weight kg
502500052030630	0.5	50-203	190	154	22	27	6.6
502500102030630	1	64-305	206	180	30	26	9.4
502500102030630	1	64-203	206	180	30	26	9.4
502500202030630	2	88-305	246	210	37	26	14.5
502500202030630	2	88-203	246	210	37	26	14.5
502500323050630	3.2	100-305	300	249	42	28	25.7
502500322030630	3.2	100-203	300	249	42	28	25.7
502500503050630	5	114-305	336	277	50	37	37.3
502500502030630	5	114-203	336	277	50	37	37.3
502501003050630	10	124-305	396	334	58	37	59
502501002030630	10	124-203	396	334	58	37	59

Blueprint

