

## Wire Rope Lifting Sling WLS-273

---

### Product information



**Standard steel wire rope construction: 6x36WS IWRC, 1960N/mm<sup>2</sup>**

**Design:** Master link in one end and thimble in other ends, aluminum ferrule secured (mechanical spliced).

Load table at Technical Data -> [Show table](#)

Please specify the needed (working) length with your request.

Other rope construction and/or end-terminations such as top rings, shackles, hooks, etc.. possible on request. In that case, please contact us to discuss the possible options or specify it with your request.

... [Read more](#)

---

## Wire Rope Lifting Sling WLS-273

### Technical data

| Part code | Diameter<br>mm | WLL<br>ton | WLL 0-45°<br>t | WLL 45-60°<br>t |
|-----------|----------------|------------|----------------|-----------------|
| 1605      | 3              | 0.16       | 0.16           | 0.12            |
| 1605      | 4              | 0.29       | 0.29           | 0.21            |
| 1605      | 5              | 0.45       | 0.45           | 0.32            |
| 1605      | 6              | 0.66       | 0.66           | 0.47            |
| 1605      | 7              | 0.89       | 0.89           | 0.64            |
| 1605      | 8              | 1.15       | 1.15           | 0.82            |
| 1605      | 9              | 1.45       | 1.45           | 1.04            |
| 1605      | 10             | 1.79       | 1.79           | 1.28            |
| 1605      | 11             | 2.17       | 2.17           | 1.55            |
| 1605      | 12             | 2.57       | 2.57           | 1.84            |
| 1605      | 13             | 3.03       | 3.03           | 2.17            |
| 1605      | 14             | 3.52       | 3.52           | 2.51            |
| 1605      | 16             | 4.6        | 4.6            | 3.3             |
| 1605      | 18             | 5.81       | 5.81           | 4.1             |
| 1605      | 20             | 7.17       | 7.17           | 5.1             |
| 1605      | 22             | 8.69       | 8.69           | 6.2             |
| 1605      | 24             | 10.33      | 10.33          | 7.38            |
| 1605      | 26             | 12.13      | 12.13          | 8.66            |
| 1605      | 28             | 14.06      | 14.06          | 10.04           |
| 1605      | 32             | 18.37      | 18.37          | 13.12           |
| 1605      | 36             | 23.23      | 23.23          | 16.59           |
| 1605      | 40             | 28.78      | 28.78          | 20.56           |
| 1605      | 44             | 34.69      | 34.69          | 24.78           |
| 1605      | 48             | 41.37      | 41.37          | 29.55           |
| 1605      | 52             | 52.04      | 52.04          | 34.69           |