

## Wire Rope Lifting Sling WLS-473

---

### Product information



**Standard steel wire rope construction: 6x36WS IWRC, 1960N/mm<sup>2</sup>**

**Design:** Master link in one end and thimble in other ends, aluminum ferrule secured (mechanical spliced).

Load table at Technical Data -> [Show table](#)

Please specify the needed (working) length with your request.

Other rope construction and/or end-terminations such as top rings, shackles, hooks, etc.. possible on request. In that case, please contact us to discuss the possible options or specify it with your request.

... [Read more](#)

---

## Wire Rope Lifting Sling WLS-473

### Technical data

Part code	Diameter mm	WLL ton	WLL 0-45° t	WLL 45-60° t
1609	3	0.25	0.25	0.18
1609	4	0.44	0.44	0.31
1609	5	0.68	0.68	0.49
1609	6	0.98	0.98	0.7
1609	7	1.34	1.34	0.96
1609	8	1.72	1.72	1.23
1609	9	2.18	2.18	1.56
1609	10	2.69	2.69	1.92
1609	11	3.25	3.25	2.32
1609	12	3.85	3.85	2.75
1609	13	4.55	4.55	3.25
1609	14	5.28	5.28	3.77
1609	16	6.9	6.9	4.93
1609	18	8.71	8.71	6.22
1609	20	10.75	10.75	7.68
1609	22	13.03	13.03	9.31
1609	24	15.5	15.5	11.07
1609	26	18.19	18.19	13
1609	28	21.08	21.08	15.06
1609	32	27.56	27.56	19.69
1609	36	34.84	34.84	24.89
1609	40	43.17	43.17	30.84
1609	44	52.04	52.04	37.17
1609	48	62.06	62.06	44.33
1609	52	75.85	75.85	52.04