CERTEX | Lifting Solutions Group
Axel Johnson International

Powertex Chain Sling G10 in Box PCSB-A-026

Product information



POWERTEX

Our smart chain sling system in Grade 10 consists of 1-leg and 2-leg slings that can be used directly from the box.

The smart slings can instantly be combined on the crane hook to lift loads that require 3 or 4 legs to be used.

Features:

- Multifunctional chain slings Grade 10 packed in box having all necessary markings and documents and ready for use
- The smart stainless steel sling tag gives information of the WLL for the sling as configurated, but also when used in any 1-4 leg PCSB combination
- Two 1-leg or 2-leg PCSB slings can easy and safely be combined on the crane hook to perform 2-leg, 3-leg and 4-leg lifting operation thanks to the smart sling tag
- 2-leg slings can also safely be used in a 1-leg lifting operation as adequate information is given on the smart sling tag (Non-used leg should be hooked to the master link to avoid snagging)
- +25% higher lifting capacity (WLL) compared to standard Grade 8 slings
- Light weight thanks to the smart, multifunctional top components
- Cost effective compared to conventional slings thanks to use of multifunctional components
- Shortening function is integrated in the master link connector allowing the chain legs to be adjusted instantly
- Shortening can be made from either side of the shortener which is a safety advantage compared to shortening clutch.
- No reduction of WLL when shortening the chains thanks to the well-

··· *Read more*

Material: Quenched and Tempered Alloy Steel of Grade 10 quality
Marking: According to standard, CE-mark, WLL, Chain size, Length, Grade 10, Serial number, MFG date, QR code leading to user manual
Temperature range: -40ºC up to +200°C without reduction of WLL
Finish: Painted blue
Standard: EN 818-4
(+ 25% WLL) and ASTM A973

Safety factor: 4:1
Grade: 10

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Powertex Chain Sling G10 in Box PCSB-A-026

Technical data

Part code	Chain diameter mm	WLL ton	EWL m	Description	Number of legs	Weight kg
240500600200010	6	1.4	2	Grab Masterlink X-A04 and Clevis Self Locking hook X-026	1	2.7
240500600300010	6	1.4	3	Grab Masterlink X-A04 and Clevis Self Locking hook X-026	1	3.6
240500600500010	6	1.4	5	Grab Masterlink X-A04 and Clevis Self Locking hook X-026	1	5.4
240800600300010	6	2	3	Grab Masterlink X-A05 and Clevis Self Locking hooks X-026	2	6.7
240800600500010	6	2	5	Grab Masterlink X-A05 and Clevis Self Locking hooks X-026	2	10.3
240500800200010	8	2.5	2	Grab Masterlink X-A04 and Clevis Self Locking hook X-026	1	4.8
240500800300010	8	2.5	3	Grab Masterlink X-A04 and Clevis Self Locking hook X-026	1	6.4
240500800500010	8	2.5	5	Grab Masterlink X-A04 and Clevis Self Locking hook X-026	1	9.6
240800800300010	8	3.55	3	Grab Masterlink X-A05 and Clevis Self Locking hooks X-026	2	11.5
240800800500010	8	3.55	5	Grab Masterlink X-A05 and Clevis Self Locking hooks X-026	2	17.9
240501000300010	10	4	3	Grab Masterlink X-A04 and Clevis Self Locking hook X-026	1	10.1
240501000600010	10	4	6	Grab Masterlink X-A04 and Clevis Self Locking hook X-026	1	17.6
240801000300010	10	5.6	3	Grab Masterlink X-A05 and Clevis Self Locking hooks X-026	2	18.1
240801000600010	10	5.6	6	Grab Masterlink X-A05 and Clevis Self Locking hooks X-026	2	33.1
240501300300010	13	6.7	3	Extra large Grab Masterlink X-001-251+X-079-13 and Self Locking hook X-026	1	18.8
240501300600010	13	6.7	6	Extra large Grab Masterlink X-001-251+X-079-13 and Self Locking hook X-026	1	31.7
240801300300010	13	9.5	3	Extra large Grab Masterlink X-001-251+X-079-13 and Self Locking hook X-026	2	34.5
240801300600010	13	9.5	6	Extra large Grab Masterlink X-001-251+X-079-13 and Self Locking hook X-026	2	60.3

© November 2026 - All Rights Reserved