



Chain Sling CSX-175 Grade 10

Product information

Design: Chain sling with master link on one end and clevis load hook on the other end. \varnothing 26 mm chain is fitted with an eye hook. Other combinations possible on demand.

Dimensions: \varnothing 6–26 mm (other dimensions on demand).

Material: Alloy steel.

Marking: According to standard, CE-marked

Temperature range: -40°C up to 200°C (up to 380° possible on demand)

Standard: EN 818-4

Warning: Not to be heat-treated.

Safety factor: 4:1

Grade: 10

Part code	Chain diameter mm	WLL ton	EWL m
240500600000080	6	1.4	-
240500600050080	6	1.4	0.5
240500600100080	6	1.4	1
240500600150080	6	1.4	1.5
240500600200080	6	1.4	2
240500600300080	6	1.4	3
240500600400080	6	1.4	4

240500600500080	6	1.4	5
240500600600080	6	1.4	6
240500700000080	7	1.9	-
240500700050080	7	1.9	0.5
240500700100080	7	1.9	1
240500700150080	7	1.9	1.5
240500700200080	7	1.9	2
240500700300080	7	1.9	3
240500700400080	7	1.9	4
240500700500080	7	1.9	5
240500700600080	7	1.9	6
240500800000080	8	2.5	-
240500800000080	8	2.5	-
240500800000080	8	2.5	-
240500800000080	8	2.5	-
240500800000080	8	2.5	-
240500800000080	8	2.5	-
240500800000080	8	2.5	-
240500800000080	8	2.5	-
240500800000080	8	2.5	-
240501000000080	10	4	-
240501000000080	10	4	-
240501000000080	10	4	-

240501600000080	16	10	-
240501900000080	19	14	-
240501900000080	19	14	-
240501900000080	19	14	-
240501900000080	19	14	-
240501900000080	19	14	-
240501900000080	19	14	-
240501900000080	19	14	-
240501900000080	19	14	-
240501900000080	19	14	-
240502200000080	22	19	-
240502200000080	22	19	-
240502200000080	22	19	-
240502200000080	22	19	-
240502200000080	22	19	-
240502200000080	22	19	-
240502200000080	22	19	-
240502200000080	22	19	-
240502200000080	22	19	-
240502600000080	26	26.5	-
240502600000080	26	26.5	-
240502600000080	26	26.5	-
240502600000080	26	26.5	-

240502600000080	26	26.5	-
240502600000080	26	26.5	-
240502600000080	26	26.5	-
240502600000080	26	26.5	-
240502600000080	26	26.5	-