Lifting Solutions Group
Axel Johnson International

Beam Clamp - IPBHZ

Product information



The IPBHZ beam clamp is used for horizontal lifting and transferring of steel beams. The base is slotted to allow the clamps to be used from end of beams as well as from the flange. This series of clamps can be used in vertical and horizontal moving, transferring and stacking of different types of structural designs, such as I-Beams, H-beams, angles, etc, depending on the application desired.

Features:
• Available in capacities of 0.75 through 12 metric tons.
• Wide variety of jaw openings available from 0 to 40 mm.
• Welded alloy steel body for strength and smaller size. Forged alloy components, where required.
• Individually Proof Tested to 2 times the Working Load Limit with certification.
• Maintenance and repair kits are available.
• All sizes are RFID EQUIPPED.

... *Read more*

Material: Alloy steel.
Marking: According to standard, CE-mark, WLL, Logo, Jaw opening, Serial number
Temperature range: -40°C up to +100°C
Standard: EN 13155
Warning: A minimum load of 10% of the WLL is required.

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Beam Clamp - IPBHZ

Blueprint



Technical data

Part code	WLL ton	Jaw width mm	Model	A mm	B mm	C mm	D mm	E mm	F mm	G mm	J mm	L mm	Weight kg
502100080250200	0.75	0-25	0.75-IPBHZ	0-25	40	148	220	50	130	69	33	22	3
502100150250200	1.5	0-25	1.5-IPBHZ	0-25	60	203	255	50	158	73	35	28	6
502100300400200	3	0-40	3-IPBHZ	0-40	80	227	325	70	188	112	38	32	10.5
502100450400200	4.5	0-40	4.5-IPBHZ	0-40	112	284	413	70	251	116	80	40	25

© November 2026 - All Rights Reserved