

## Beam Clamp - IPTKW

---

### Product information



The IPTKW series beam clamp is suitable for use as a temporary tackle eye for a beam and it is an economy version of the IPTK model.

#### Features:

- Available in capacities of 2 thru 5 metric tons.
- Wide variety of jaw openings available: 75 to 350 mm.
- Welded alloy steel body for strength and smaller size. Forged alloy components, where required.
- Individually Proof Tested to 2 times the Working Load Limit with certification.
- User manual with test certificate is included with each clamp.
- Maintenance and repair kits are available.
- All sizes are RFID EQUIPPED.

... [Read more](#)

---

**Material:** Alloy steel


**Marking:** According to standard, CE-marked, WLL, Logo, Jaw opening, Serial number

**Temperature range:** -40°C up to +100°C

**Standard:** EN 13155

## Beam Clamp - IPTKW

### Blueprint



### Technical data

Part code	WLL ton	Jaw width mm	Model	A mm	C mm	D mm	F mm	H mm	Weight kg
502100201900220	2	75-190	2-IPTKW	75-190	A+80	125	28	25	4
502100301900220	3	75-190	3-IPTKW	75-190	A+80	125	28	25	4.5
502100402800220	4	150-280	4-IPTKW	150-280	A+100	125	33	35	6.3
502100503500220	5	120-350	5-IPTKW	120-350	A+195	125	33	40	8.8