

Beam Clamp - IPTK

Product information



This IPTK series beam clamp is suitable for use as a temporary tackle eye for horizontal lifting and transportation of steel (H) beams, profiles and structures. Can also be used as upside down attached (temporary) lifting point.

Features:

- Available in capacities of 2 through 25 metric tons.
- Wide variety of jaw openings available: 75 to 1020 mm.
- Welded alloy steel body for strength and smaller size. Forged alloy components, where required.
- Individually Proof Tested to 2 times the Working Load Limit with certification.
- User manual with test certificate is included with each clamp.
- Maintenance and repair kits are available.
- All sizes are RFID EQUIPPED.

... [Read more](#)

Material: Steel


Marking: According to standard, CE-marked, WLL, Logo, Jaw opening, Serial number

Temperature range: -40°C up to +100°C

Standard: EN 13155

Beam Clamp - IPTK

Blueprint



Technical data

| Part code | WLL ton | Jaw width mm | Model | A mm | C mm | D, mm | E mm | H, mm | K mm | Weight kg |
|-----------------|---------|--------------|---------|----------|-------|-------|------|-------|------|-----------|
| 502100201900230 | 2 | 75-190 | 2-IPTK | 75-190 | A+80 | 125 | 75 | 25 | 20 | 6 |
| 502100301900230 | 3 | 75-190 | 3-IPTK | 75-190 | A+80 | 125 | 75 | 25 | 20 | 6.5 |
| 502100402800230 | 4 | 150-280 | 4-IPTK | 150-280 | A+100 | 125 | 75 | 35 | 20 | 8.5 |
| 502100503500230 | 5 | 120-350 | 5-IPTK | 120-350 | A+195 | 125 | 75 | 40 | 20 | 11 |
| 502102501020230 | 25 | 450-1,020 | 25-IPTK | 450-1020 | A+220 | 500 | 125 | 76 | 45 | 225 |