

Horizontal Lifting Clamp IPHOZ

Product information



The IPHOZ horizontal lifting clamp is to be used for lifting and transferring, in the horizontal position, of thin sheet and other materials that will sag or bend when lifted. These clamps must be used in pairs or more.

Features:

- Available in capacities of 0.75 through 15 metric tons
- Wide variety of jaw openings available: 0 to 60mm
- Welded alloy steel body for strength and smaller size. Forged alloy components, where required
- Individually Proof Tested to 2 times the Working Load Limit with certification
- User manual with test certificate is included with each clamp
- Maintenance and repair kits are available
- All sizes are RFID EQUIPPED

... [Read more](#)

Material: Alloy steel

Marking: According to standard, CE-marked, WLL, Logo, Jaw opening, Serial number


Temperature range: -40°C up to +100°C

Standard: EN 13155

Warning: Only to be used in pairs.

Horizontal Lifting Clamp IPHOZ

Blueprint



Technical data

Part code	WLL ton	Jaw width mm	Model	A mm	B mm	C mm	E mm	F mm	G mm	H mm	J mm	K mm	L mm	Weight kg
502100080300300	0.75	0-30	0.75-IPHOZ	0-30	94	16	16	70	118	81	12	31	12	3
502100150450300	1.5	0-45	1.5-IPHOZ	0-45	133	16	22	125	192	100	16	36	12	5.5
502100300450300	3	0-45	3-IPHOZ	0-45	137	20	26	125	200	120	20	48	10	8
502100450450300	4.5	0-45	4.5-IPHOZ	0-45	138	25	30	126	220	120	20	50	10	9.5
502100600600300	6	0-60	6-IPHOZ	0-60	171	30	36	135	235	130	20	56	20	15.5
502100900600300	9	0-60	9-IPHOZ	0-60	211	30	43	166	276	160	25	62	20	25
502101200600300	12	0-60	12-IPHOZ	0-60	217	40	47	168	294	190	25	62	19	29
502101500600300	15	0-60	15-IPHOZ	0-60	-	-	-	-	-	-	-	-	-	38