

## Screw Pin Chain Shackle Crosby G-210

### Product information

**Design:** Screw pin anchor shackles meet the performance requirements of Federal Specification RR-C-271G Type IVA, Grade A, Class 2, except for those provisions required of the contractor.

**Material:** Forged - Quenched and Tempered, with alloy pins.

**Marking:** According to standard, CE-marked

**Temperature range:** -40° C to 204° C

**Finish:** Hot Dip galvanized or self colored.

**Standard:** EN 13889, US. FED. SPEC. RR-C-271F

**Safety factor:** 6:1

**Grade:** 6



Part code	WLL ton	Size inch	A	B mm	C mm	D mm	F mm	G mm	H mm	L	M mm	P mm	Weight kg	Delivery time
420100050030	0.5	1/4	12	8	22	6	16	25	40	5	36	6	0.05	2
420100750030	0.75	5/16	14	10	26	8	19	29	48	6	43	8	0.08	2
420100100030	1	3/8	17	11	32	10	23	36	59	6	52	10	0.13	-
420100150030	1.5	7/16	19	13	37	11	27	41	68	8	60	11	0.2	2
420100200030	2	1/2	21	16	41	13	30	46	77	10	68	13	0.27	-
420100330030	3.25	5/8	27	19	51	16	38	59	96	11	85	16	0.57	-
420100480030	4.75	3/4	32	22	60	19	46	70	115	13	101	21	1.03	2
420100650030	6.5	7/8	37	25	71	22	53	81	135	13	114	25	1.43	2
420100850030	8.5	1	43	29	81	25	60	94	151	14	130	25	2.15	-
420100950030	9.5	1 1/8	46	32	90	29	68	103	172	16	152	32	3.06	2
420101200030	12	1 1/4	52	36	100	32	76	115	191	18	165	35	4.11	2
420101350030	13.5	1 3/8	57	40	111	35	84	127	210	19	176	38	5.28	-
420101700030	17	1 1/2	60	42	124	38	92	137	230	21	189	41	7.23	2
420102500030	25	1 3/4	73	52	146	44	106	162	279	25	233	54	12.1	-
420103500030	35	2	83	58	171	53	127	184	324	29	263	60	19.2	-
420105500030	55	2 1/2	105	71	203	67	144	238	377	35	335	67	32.5	-

## Blueprint

