



## Screw Pin Anchor Shackle Crosby G-209

### Product information

Screw pin anchor shackles meet the performance requirements of Federal Specification RR-C-271G Type IVA, Grade A, Class 2, except for those provisions required of the contractor.

**Proof load:** 2 x WLL.

**Material:** Carbon steel with headbolt in alloy steel.

**Marking:** According to standard, CE-marked

**Temperature range:** -40°C up to +204°C

**Finish:** Hot dip galvanized.

**Standard:** EN 13889

**Safety factor:** 6:1

**Grade:** 6

| Part code    | WLL<br>ton | Size<br>inch | Weight<br>kg | Delivery time |
|--------------|------------|--------------|--------------|---------------|
| 420100030190 | 0.33       | 3/16         | 0.03         | 2             |
| 420100050190 | 0.5        | 1/4          | 0.05         | 2             |
| 420100750190 | 0.75       | 5/16         | 0.09         | 2             |
| 420100100190 | 1          | 3/8          | 0.14         | 2             |
| 420100150190 | 1.5        | 7/16         | 0.17         | 2             |
| 420100200190 | 2          | 1/2          | 0.33         | 2             |
| 420100330190 | 3.25       | 5/8          | 0.62         | 2             |
| 420100480190 | 4.75       | 3/4          | 1.07         | 2             |
| 420100650190 | 6.5        | 7/8          | 1.64         | 2             |
| 420100850190 | 8.5        | 1            | 2.28         | 2             |
| 420100950190 | 9.5        | 1 1/8        | 3.36         | 2             |
| 420101200190 | 12         | 1 1/4        | 4.31         | 2             |
| 420101350190 | 13.5       | 1 3/8        | 6.14         | 2             |
| 420101700190 | 17         | 1 1/2        | 7.8          | 2             |
| 420102500190 | 25         | 1 3/4        | 12.6         | -             |
| 420103500190 | 35         | 2            | 20.4         | 2             |
| 420105500190 | 55         | 2 1/2        | 38.9         | 2             |

## Blueprint

