



Wire Rope Clip Crosby G-450

Product information

Based on the catalog breaking strength of wire rope, Crosby wire rope clips have an efficiency rating of 80% for 3 mm through 22 mm sizes, and 90% for sizes 24 mm through 90 mm.

Features: Wire clips to secure and form a temporary termination on site.

Material: Steel

Marking: According to standard, ID code and Manufacturer's symbol

Finish: Galvanised

Standard: EN 13411-5

Note: All sizes except 68-72 mm and 85-90 mm meet the performance requirements of EN13411.

Part Code	Rope diameter mm	A mm	B mm	C mm	D mm	E mm	F mm	G mm	H mm	Weight kg/100pc	Delivery time
--	3-4	5.6	18.3	11.2	11.9	10.4	9.65	20.6	23.9	2.72	3
--	5	6.35	24.6	14.2	15	12.7	11.2	23.9	29.5	4.54	3
--	6-7	7.85	26.2	12.7	19.1	16.8	14.2	30.2	36.6	8.62	3
--	8	9.65	35.1	19.1	22.4	18.3	17.5	33.3	42.9	12.7	3
--	9-10	11.2	38.1	19.1	25.4	23.1	19.1	41.4	49.3	21.8	3
--	11-13	0.5	1.88	1	1.19	1.13	0.88	1.91	2.28	80	3
--	14-16	0.56	2.25	1.25	1.31	1.34	0.94	2.06	2.5	110	3
--	18-20	15.7	70	36.6	38.1	35.8	26.9	57	72	64	3
--	22	19.1	79	41.1	44.5	40.4	31.8	62	80.5	96	3
--	24-26	19.1	89	46	47.8	45.2	31.8	67	88	114	3
--	28-30	19.1	98.5	51	51	48.5	31.8	71.5	91	128	3
--	32-34	22.4	108	54	59.4	55.5	36.6	79.5	105	199	3
--	36	22.4	118	58.5	59.4	58.5	36.6	79.5	106	200	3
--	38	22.4	125	60.5	66.5	62	36.6	86.5	113	247	3
04E0289	44-46	28.7	146	70	77.5	74.5	46	97	134	424	3
04E0290	48-52	31.8	164	76	86	77	51	113	149	590	3
--	56-58	31.8	181	81	98.5	81	51	114	162	726	3
--	62-65	31.8	195	87.5	105	93.5	51	119	168	862	3
--	68-72	31.8	211	90.5	111	124	51	127	175	1,043	3
--	75-78	38.1	233	98.5	121	119	60.5	149	194	1,406	3
--	85-90	38.1	273	114	140	152	60.5	157	213	1,814	3

Blueprint

