

Eye Bolt Shoulder Type Machinery Crosby S-279 UNC

Product information



Working Load Limits shown are for in-line pull.
Recommended for straight line pull.
Fatigue rated at 1 1/2 times the Working Load Limit at 20,000 cycles.
Standard bolts threaded UNC.


[... Read more](#)

Material: Forged Steel – Quenched & Tempered.

Safety factor: 4:1

Eye Bolt Shoulder Type Machinery Crosby S-279 UNC

Blueprint



Technical data

Part code	WLL ton	Thread Inch	B mm	C mm	D, mm	E mm	F mm	G, mm	H, mm	Weight kg
421100070210	0.7	3/8 - 16	32.3	41.1	25.4	78	7.85	17.5	26.7	0.06
421100120210	1.18	1/2 - 13	38.9	49.5	30.2	94	9.65	23.1	32.3	0.12
421100240210	2.35	5/8 - 11	45.5	60.5	35.1	113	12.7	28.7	38.9	0.24
421100330210	3.26	3/4 - 10	52	70	38.1	129	16	35.1	43.4	0.43
421100480210	4.8	7/8 - 9	58.5	82.5	44.5	149	19.1	39.6	50.8	0.7
421100600210	6.03	1 - 8	65.5	95.5	51	169	22.4	46	58.4	1.1
421100680210	6.8	1-1/8 - 7	69.8	107	57.1	183	24.6	52.3	59.7	1.5
421100950210	9.52	1-1/4 - 7	78.5	114	63.5	202	25.4	58	69.3	1.8

Eye Bolt Shoulder Type Machinery Crosby S-279 UNC

M-279 Metric

Stock Code	Size mm	Working Load Limit t	Dimensions (mm)		Weight kg	E	F	G	H		
			B	C							
11.401045753	M6	0,2	13	28.7	19.1	47	4.9	13.5	19.6	0.03	
11.401045789	M8	0,4	13	35.1	22.4	54.6	6.4	15	24.1	0.05	
11.401045831	M10	0,64	17	41.1	25.4	64.3	7.9	17.5	26.5	0.07	
11.401045861	M12	1	20.5	49.5	30.2	77.7	9.7	23.1	32.8	0.11	
11.401045911	M16	1,8	27	60.5	35.1	96	12.7	28.7	38.9	0.25	
11.401045991	M20	2,5	30	70	38.1	108	16	35.1	43.4	0.42	
11.401046021	M24	4	36	95.5	51	142	22.4	46	58.4	1.05	
11.401046031	M27	5	69.8	107	57.1	183	24.6	52.3	59.7	1.42	
11.401046071	M30	6	45	114	63.5	171	25.4	58	69.3	1.77	
11.401046101	M36	8.5	54	140	76	207	31.8	70	83.3	3.12	
11.401046111	M42	14	95.2	159	88.9	266	35	76.2	91.4	4.58	
11.401046121	M48	17.3	102	194	101	313	46	85.9	114	8.71	
11.401046131	M64	29.5	127	223	114	378	53.8	108	140	14.74	