



Open Spelter Socket McKissick G-416

Product information

Standard: Fed Spec RR-S-550D TYPE A.

Features: Spelter socket terminations have an efficiency rating of 100%, based on the catalogue strength of wire rope.

Material: Forged steel sockets through 1 1/2", cast alloy steel 1-5/8" through 4".

Marking: ID code and Manufacturer's symbol.

Finish: Galvanised.

Part code	Rope Ø range mm	MBL	Finish	Rope Ø inch	Weight kg
122101000062	8-10	12	Galvanized	5/16 - 3/8	0.59
122101300062	11-13	20	Galvanized	7/16 - 1/2	1.02
122101600062	14-16	27	Galvanized	9/16 - 5/8	1.863
122101800062	18	43	Galvanized	3/4	2.64
122102200062	20-22	55	Galvanized	7/8	4.438
122102600062	24-26	78	Galvanized	1	7.03
122103000062	28-30	92	Galvanized	1 1/8	9.75
122103500062	32-35	136	Galvanized	1 1/4 - 1 3/8	14.1
122103800062	38	170	Galvanized	1 1/2	21.4
122104200062	40-42	188	Galvanized	† 1 5/8	24.9
122104800062	44-48	268	Galvanized	† 1 3/4 - 1 7/8	37.2
122105400062	50-54	291	Galvanized	† 2 - 2 1/8	59
122106000062	56-60	360	Galvanized	† 2 1/4 - 2 3/8	76
122106700062	64-67	424	Galvanized	† 2 1/2 - 2 5/8	114
122107300062	70-73	511	Galvanized	† 2 3/4 - 2 7/8	143
122108000062	75-80	563	Galvanized	† 3 - 3 1/8	172
122108600062	82-86	722	Galvanized	† 3 1/4 - 3 3/8	197
122109200062	88-92	779	Galvanized	† 3 1/2 - 3 5/8	255
122110200062	94-102	875	Galvanized	† 3 3/4 - 4	355

Blueprint

