

Swage Button S-409

Product information



General:

- Swage button terminations have an efficiency rating of 98% based on the catalog strength of wire rope.
- Special processed, low carbon steel.
- COLD TUFF for better swageability.
- Stamp for identification after swaging without concern for fractures (as per directions in the wire rope end terminations user's manual).

Note: Length is measured from outside end of termination.

Part code	Rope Ø range	Size	Description	A mm	B mm	C mm	D mm	E mm	Weight kg/100pc	Delivery time
12051040171	3	1 SB	1/8 - 1/4 Button	10.7	12.7	3.56	10.2	15.5	0.91	-
12051040215	5	3 SB	1/4 1st Stage	14.2	17.8	5.08	13.2	21.3	1.81	-
12051040251	6-7	5 SB	1/8 - 1/4 Button	17.3	26.9	7.87	14.7	33.5	3.63	-
12051040297	8	7 SB	3/8 1st Stage	22.4	28.7	9.14	19.6	33.8	7.26	-
12051040313	9-10	8 SB	3/8 1st Stage	22.4	37.6	10.7	19.6	42.9	6.8	-
12051040331	11	9 SB	1/2 1st Stage	28.7	41.4	12.2	26.2	49.3	13.6	-
12051040359	13	10 SB	5/8 Socket	33.3	48	14	29.5	55.1	22.7	-
12051040377	14	11 SB	9/16 - 5/8 Button	36.6	51.3	15.5	32.8	61.2	31.8	-
12051040395	16	12 SB	3/4 Socket	39.6	61.5	17	36.1	73.4	45.4	-
12051040411	18-20	13 SB	3/4 1st Socket	42.7	69.6	20.3	39.6	82.6	59	-
12051040439	22	14 SB	7/8 1st Stage	50.8	83.1	23.9	45.7	98	100	-
12051040457	25-26	15 SB	1 1st Stage	57.2	93.2	26.9	52.1	111	141	3
12051040475	28-29	16 SB	1-1/8 1st Stage	65	103	30.2	58.4	122	204	-
12051040493	31-32	17 SB	1-3/8 Socket	71.4	116	33.8	65	138	295	3

Blueprint

