



E50

Evacuator® rescue device for high structures 50 - 300 m

Product information

Evacuator is the only fireproof escape device for more people and heights up to 300 mtr.

The Evacuator® utilises a user-friendly 'click on and go' mechanism. Each steel cable allows multiple persons to descent at the same time, providing their combined weight does not exceed 282 Kg on each steel cable / escape-hook. The total max. descent load on the system is 564 Kg.

It is available in three models:

Model E50 equipped with 4 cable reels.

Models E140/E165 equipped with 2 cable reels.

Model E300 equipped with 1 cable reel.

Features:

- Pre-installed at the escape area: Ready for immediate use in case of emergency.
- Controlled descent speed approx. 1 m/sec.
- Max. load per reel 254 kg > 2 to 3 adults at a time, or 2 adults + 2 kids.
- No electricity required. Works at all times.
- Installation inside or outside / weatherproof.
- Compact, easy to install and maintenance friendly.
- Long service life, cost efficient.
- Pricing competitive with traditional rope-based descenders.
- High quality. Useful for any industrial or civic application.

Any ppe can be supplied together with the Evacuator.

Ask for more information:

leaflets

video's

demonstration.

Marking: According to standard, CE-marked

Standard: EN ISO 7149

Part Code	Length m	Model	Maximum occupancy	Ropes	SWL (per rope)
821505000050	50	E50	16 people (max weight per rope 282 kg)	4	282 kg
821514000050	140	E140	8 people (max weight per rope 282 kg)	2	282 kg
821530000050	300	E300	4 people (max weight per rope 282 kg)	1	282 kg