Lifting Solutions Group
Axel Johnson International

Spreader Beams - Modular

Product information



Modulift Spreader Systems are a cost-effective and flexible option for lifting objects where there is a possibility of crushing the load.
The modular concept is based on the assembly of a pair of end units, which provide the connection between the top and the bottom slings, and a combination of struts of different length bolted between the end units to achieve variable length capability. In use, the bolts do not carry any of the lifting forces but simply connect the assembly together while the geometry of the system does the work.

The Modulift Spreader System enables slings to connect to large and bulky objects in a vertical attitude. Built using a unique
engineering formula, the spreaders are designed using their lightweight structure to resist the compression forces of the lifting arrangement. The design utilises one of the most basic structural engineering elements, that of a pin-ended strut.

The shackles, which connect the top slings to the spreader, provide the pin and give flexibility to the geometry of the slings which prevents bending forces being generated by the lifting process and transmitted into the object being lifted.
Modulift Spreaders are optimised for weight at every size. The unique capabilities of the Modular system add to it's benefits through easier and more manoeuvrable ground handling, easy build and storage capabilities and with a range of components to make up the spreader, gives it a multi-use feature and a costeffective solution over a range of lifts.

The Modulift range comprises 16 systems, which provide lifting capacity for weights between 2 – 3000 tonnes and lengths
from 0.2m to 45m. The system is used for the smallest maintenance work to the largest lifting jobs in many industry sectors
including construction, maritime, offshore, oil & gas, industrial and aerospace industries. All utilise the modular system
to enable the lifting of various loads, without the need to buy or rent ne ... *Read more*

© November 2026 - All Rights Reserved

Spreader Beams - Modular

Technical data

Code	Type
MOD 6	Mini
MOD 12	Portable
MOD 24	Portable
MOD 34	Portable
MOD 50	Heavy range
MOD 70	Heavy range
MOD 70H	Heavy range
MOD 110	Heavy range
MOD 110H	Heavy range

Technical information

Mini

© November 2026 - All Rights Reserved

Spreader Beams - Modular

Part	Mini	
	MOD 6	
	Length [m]	Weight [kg]
item	0,1	2,0
item	0,2	2,7
item	0,3	3,4
item	0,6	5,4
item	1,0	8,1
end unit (x2)	0,2	3,0
drop link (x2)	0,0	0,6
upper shackle (x2)	0,0	1,1
lower shackle (x2)	0,0	0,7
length min-max [m]	0,4 - 2,5	
upper shackle	4,75 t	
lower shackle	3,25 t	
torque [Nm]	60	
wrench width [mm]	17	

Portable

© November 2026 - All Rights Reserved

Spreader Beams - Modular

Part	Portable range					
	MOD 12		MOD 24		MOD 34	
	Length [m]	Weight [kg]	Length [m]	Weight [kg]	Length [m]	Weight [kg]
item	0,3	6,0	0,5	16	0,5	20
item	0,5	8,0	1,0	24	1,0	31
item	0,8	11,0	2,0	41	2,0	51
item	1,0	14,0	-	-	-	-
item	1,5	19,0	-	-	-	-
end unit (x2)	0,3	6,0	0,5	16	0,5	23
drop link (x2)	0,0	1,5	0,0	4	0,0	4
upper shackle (x2)	0,0	2,5	0,0	8	0,0	14
lower shackle (x2)	0,0	1,5	0,0	5	0,0	8
length min-max [m]	0,5 - 4		1 - 6		1 - 8	
upper shackle	8,5 t		17 t		25 t	
lower shackle	6,5 t		12 t		17 t	
torque [Nm]	90		150		150	
wrench width [mm]	19		30		30	

Heavy Range

© November 2026 - All Rights Reserved

Spreader Beams - Modular

Part	Heavy range									
	MOD 50		MOD 70		MOD 70H		MOD 110		MOD 110H	
	Length [m]	Weight [kg]	Length [m]	Weight [kg]	Length [m]	Weight [kg]	Length [m]	Weight [kg]	Length [m]	Weight [kg]
item	0,5	38	0,5	61	0,5	61	1,0	134	1,0	134
item	1,0	53	1,0	85	1,0	85	2,0	212	2,0	212
item	2,0	82	2,0	136	2,0	136	4,0	367	4,0	367
item	4,0	140	4,0	240	4,0	240	-	-	-	-
item	-	-	-	-	-	-	-	-	-	-
end unit (x2)	0,5	38	0,5	56	0,5	56	1,0	178	1,0	178
drop link (x2)	0,0	11	0,0	17	0,0	32	0,0	45	0,0	55
upper shackle (x2)	0,0	19	0,0	38	0,0	62	0,0	62	0,0	110
lower shackle (x2)	0,0	14	0,0	19	0,0	38	0,0	38	0,0	62
length min-max [m]	1 - 11		1 - 12		1 - 12		2 - 16		2 - 16	
upper shackle	35 t		55 t		85 t		85 t		120 t	
lower shackle	25 t		35 t		55 t		55 t		85 t	
torque [Nm]	150		150		150		150		150	
wrench width [mm]	30		30		30		30		30	

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Spreader Beams - Modular

© November 2026 - All Rights Reserved