Lifting Solutions Group
Axel Johnson International

# Gantry Crane, Porta Gantry 500-5000kg

**Product information**




Lightweight Gantry Crane for lifting of goods and persons. The PORTAGANTRY has the ability to be moved under load. (Subject to detailed instruction and supervision by a competent person).

**Goods WLL:** 500kg up to 5000kg (depending on model)
**Personnel WLL:** Maximum combined personnel lifting capacity up to 2500kg (depending on model)
**3-5 Person fall arrest:** EN795:1997 certified – as part of an EN363 compliant system (500 & 1000 - 3 persons, 2000, 3000 & 5000 - 5 persons)
**ATEX:** All models suitable for use in ATEX Zone 2 explosive atmospheres
**Lightweight & portable**: With easy on-site assembly within manual handling guidelines:
- 4 portable parts assembled on just 4 bolts
- Simple ‘scissoring’ assembly in just 2-3 minutes

**Ergonomic**
- 360° swivel-locking castors as standard
- Simple, manual height & span adjustment
- Ultra-safe captive trolley
- Ergonomic design of profiles and handles

**Stable:** Bolted structure, lateral beam and leg bracing features
**Configurations:** Variety of standard configurations available, plus customisation for specific requirements and interchangeable components (subject to WLL rating)
**Availability:** 14 Days

... *Read more*

© November 2026 - All Rights Reserved

CERTEX | Lifting Solutions Group
Axel Johnson International

# Gantry Crane, Porta Gantry 500-5000kg

## Technical data

| Part code | WLL ton | Model | Max load kg | A-Frame weight | Max. number of persons | Standard Beam Length mm | Min height mm | Max height mm | overall span m | Weight kg |
|---|---|---|---|---|---|---|---|---|---|---|
| 6015PGAS00500S2500A | 0.5 | A-frame S | 250 | 32 | 3 | 2,500 | 1,595 | 2,345 | 1.58 | 89 |
| 6015PGAS00500S3000A | 0.5 | A-frame S | 250 | 32 | 3 | 3,000 | 1,595 | 2,345 | 2.08 | 93 |
| 6015PGAS00500S3920A | 0.5 | A-frame S | 250 | 32 | 3 | 3,920 | 1,595 | 2,345 | 3 | 100 |
| 6015PGAS00500S4570A | 0.5 | A-frame S | 250 | 32 | 3 | 4,570 | 1,595 | 2,345 | 3.65 | 104 |
| 6015PGAS00500M2500A | 0.5 | A-frame M | 250 | 42 | 3 | 2,500 | 2,091 | 2,841 | 1.58 | 109 |
| 6015PGAS00500S5500A | 0.5 | A-frame S | 250 | 32 | 3 | 5,500 | 1,595 | 2,345 | 4.58 | 111 |
| 6015PGAS00500S6000A | 0.5 | A-frame S | 250 | 32 | 3 | 6,000 | 1,595 | 2,345 | 5.08 | 115 |
| 6015PGAS00500S8400A | 0.5 | A-frame S | 250 | 32 | 3 | 8,400 | 1,595 | 2,345 | 7.48 | 132 |
| 6015PGAS00500S9000A | 0.5 | A-frame S | 250 | 32 | 3 | 9,000 | 1,595 | 2,345 | 8.08 | 137 |

© November 2026 - All Rights Reserved