

Blocstop™ BSA Fall Arrest Device

For man riding applications a protective secondary safety device is mandatory. For this use Tractel offers the BSA Blocstop™. In response to the most strict safety regulations, it can easily be attached to most fittings. The «Tirfor®» jaw-type unit fitted inside the Blocstop™ closes onto the safety wire rope and as the jaws grip over a large area causes no damage to the wire rope.

The BSA models use two ropes, a load wire rope and a safety wire rope. The BSA Blocstop™ remains free on the safety wire rope as long as the BSA-lever is supported in its open position by the load carrying wire rope. A broken load wire rope will instantly result in closing the jaws in the BSA Blocstop™ and the load is safely arrested.

Max. load 500 kg up to 3.200 kg.

Operates automatically when there is slack wire rope or an inclined platform.



Select a row from the table below, then click the add to quote button

Part Code	Model	Wire rope diameter mm	Capacity man riding (kg)	Weight kg
--	BSA 15.301	8,3	600	4
--	BSA 20.303	9,5	800	6
--	BSA 20.304	10,2	1	6
--	BSA 20.301	11,5	1.2	6
--	BSA 35.304	14,3	2	10.6
--	BSA 35.30	16,3	2.4	10.6

1

Add to quote

Unit C1, Harworth Industrial Estate
Bryans Close
Harworth
Doncaster
DN11 8RY

01302 756 777
info@certex.co.uk