

## Vertical Lifting Clamp IP10(J)



The IP10 series vertical lifting clamps are used for the lifting, turning, moving or vertical transfer of sheet, plates, or fabrications from horizontal to vertical and down to horizontal (180°) as needed. Usually used as a single point pick or when used with a spreader beam with multiple vertical drop lines. Available in a variety of models:

- IP10 - Standard clamp for materials with a surface hardness to 363HV10 (345 HB).
- IP10J - Larger jaw opening.
- IP10S - For use with Stainless Steel material.
- IP10H - For use with materials with a surface hardness to 472HV10 (450 HB).

### Features:

- Available in capacities of .5 thru 30 metric tons
- Higher Working Load Limits are available upon request.
- Wide variety of jaw openings available: 0 to 155mm.
- Welded alloy steel body for strength and smaller size. Forged alloy components, where required.
- Individually Proof Tested to 2 times the Working Load Limit with certification.
- User manual and test certificate included with each clamp.
- Full 180° turning range for material transfer, turning or moving.
- Lock open, lock closed ability with latch for pretension on material and then release of material.
- For plate surface hardness till 279HV10, only 5% min. WLL is needed.
- Maintenance and repair kits are available.
- All sizes are RFID EQUIPPED.

**Material:** Alloy Steel.

**Marking:** According to standard, CE-marked

**Standard:** EN 13155

**Warning:** A minimum load of 10% of the WLL is required.



Select a row from the table below, then click the add to quote button

Part Code	WLL ton	IP Model.	Jaw width (mm)	B mm	C mm	D mm	E mm	F mm	G mm	H mm	J mm	K mm	Weight kg
06D0130	0.5	0.5-IP10	0-16	44	130	203	40	115	42	28	-	11	1.8
06D0140	1	1-IP10	0-20	45	139	212	40	127	42	38	-	11	2.2
06D0150	2	2-IP10	0-35	78	201	330	70	188	64	55	-	16	7.6
06D0160	3	3-IP10	0-40	100	253	434	75	222	78	60	-	20	13.8
06D0170	4.5	4.5-IP10	0-40	100	253	434	75	227	82	65	-	20	15
06D0180	6	6-IP10	0-50	126	302	517	80	292	84	95	40	20	23.5
--	6	6-IP10J	50-100	126	302	506	80	336	84	95	40	20	24.5
--	9	9-IP10	0-50	126	325	545	80	310	94	104	44	25	27.5
--	9	9-IP10J	50-100	126	325	542	80	360	94	105	44	25	28.5
--	12	12-IP10	0-54	160	392	574	80	433	121	137	41	25	49
--	12	12-IP10J	54-108	178	438	620	80	491	121	136	41	25	58
06D0185	16	16-IP10	5-64	180	463	686	88	492	121	153	49	25	68
--	16	16-IP10J	64-128	208	521	734	88	562	121	160	45	25	80
--	22.5	22.5-IP10	5-80	222	554	803	110	565	153	186	54	30	124
--	22.5	22-IP10J	80-155	255	628	883	110	660	139	196	49	25	131
--	30	30-IP10	5-80	222	554	803	110	565	153	186	54	30	124
--	30	30-IP10J	80-155	255	628	887	110	660	153	196	54	30	147

1

Add to quote







