

## Crosby HG-226, Eye / Eye



**Design:** Eye-eye. End fittings are quenched and tempered, bodies heat treated by normalizing.

**Proof:** 2 x WLL.

**Standard:** According to Federal Specifications FF-T-791b.

**Marking:** Logo, size and type.

**Finish:** Hot dipped galvanized.

**Note:** Turnbuckles recommended for straight or in-line pull only.

**Safety factor:** 5:1.



Select a row from the table below, then click the add to quote button

Part Code	WLL t ton	Thread dia. & take up (mm)	Thread dia. & take up (inch)	A mm	J open	K closed	M open	N closed	R (mm)	S (mm)	X closed	BB (mm)	Weight kg
--	0.23	6,35 x 102	1/4 x 4	6,35	303	202	314	213	20,6	8,64	44,6	103	0.13
--	0.36	7,94 x 114	5/16 x 4-1/2	7,94	354	239	368	253	24,1	11,2	55,8	116	0.22
--	0.54	9,53 x 152	3/8 x 6	9,53	446	294	463	311	28,7	13,5	62,9	115	0.34
--	1	12,7 x 152	1/2 x 6	12,7	506	354	529	376	35,8	18,0	90,4	153	0.78
--	1	12,7 x 305	1/2 x 12	12,7	819	514	841	536	35,8	18,0	89,9	314	1.19
--	1.59	15,9 x 152	5/8 x 6	15,9	552	399	577	425	45,7	22,4	110	153	1.25
--	1.59	15,9 x 305	5/8 x 12	15,9	865	560	891	586	45,7	22,4	110	315	1.87
--	2.36	19,1 x 152	3/4 x 6	19,1	590	438	622	470	53,1	25,4	130	156	1.91
--	2.36	19,1 x 305	3/4 x 12	19,1	905	600	937	632	53,1	25,4	129	320	2.78
--	2.36	19,1 x 457	3/4 x 18	19,1	1,210	753	1,242	785	53,1	25,4	130	471	3.55
--	3.27	22,2 x 305	7/8 x 12	22,2	932	627	970	665	60,5	31,8	147	309	4.01
--	3.27	22,2 x 457	7/8 x 18	22,2	1,249	792	1,287	830	60,5	31,8	147	473	5.22
--	4.54	25,4 x 152	1 x 6	25,4	666	514	711	559	76,2	36,3	165	157	4.36
--	4.54	25,4 x 305	1 x 12	25,4	971	666	1,016	711	76,2	36,3	165	309	5.88
--	4.54	25,4 x 457	1 x 18	25,4	1,276	819	1,321	864	76,2	36,3	165	462	7.4
--	4.54	25,4 x 610	1 x 24	25,4	1,596	987	1,641	1,031	76,2	36,3	164	631	9.14
--	6.89	31,8 x 305	1-1/4 x 12	31,8	1,070	766	1,127	822	91,2	46,2	216	306	9.01
--	6.89	31,8 x 457	1-1/4 x 18	31,8	1,375	918	1,432	975	91,2	46,2	216	459	10.8
--	6.89	31,8 x 610	1-1/4 x 24	31,8	1,694	1,085	1,751	1,141	91,2	46,2	216	625	12.6
--	9.71	38,1 x 305	1-1/2 x 12	38,1	1,124	819	1,187	882	104	53,8	240	313	13
--	9.71	38,1 x 457	1-1/2 x 18	38,1	1,428	971	1,492	1,035	104	53,8	240	465	15.4
--	9.71	38,1 x 610	1-1/2 x 24	38,1	1,749	1,139	1,813	1,203	104	53,8	240	633	17.9
--	12.7	44,5 x 457	1-3/4 x 18	44,5	1,457	1,000	1,534	1,076	118	60,5	253	467	23
--	12.7	44,5 x 610	1-3/4 x 24	44,5	1,762	1,153	1,838	1,229	118	60,5	253	619	26.4
--	16.8	51,01 x 610	2 x 24	50,8	1,922	1,313	2,011	1,402	148	68,3	331	622	37.9
--	27.2	63,5 x 610	2-1/2 x 24	63,5	2,011	1,402	2,113	1,503	165	79,2	350	625	67.4
--	34.01	70,0 x 610	2-3/4 x 24	69,9	2,066	1,456	2,180	1,571	178	82,6	383	626	79.1

1

Add to quote

