

## Electric Chain Hoist KITO ED Series

# KITO

**General:** The KITO ED electric chain hoist is compact, light-weight, reliable and weather- and corrosion-resistant. It has an aluminum gearbox, high performance mechanical brake, adjustable speed built-in potentiometer and a maximal speed of 20,1 m/min. The hook suspension type is offered with single or dual lifting speed. The cylinder control type (EDC) is offered with dual lifting speed.

**Options:**

- Plain trolley
- Geared trolley
- Canvas chain bucket up to 70 m
- Steel chain bucket
- Radio remote control

**Marking:** According to standard, Type plate with WLL, CE-marking and serial number.

**Finish:** Nickel plated load chain grade 80 (DAT) in accordance with EN 818-7.

**Standard:** EN 818-7



Select a row from the table below, then click the add to quote button

Part Code	Code	WLL	Lifting height m	Model	Headroom mm	Chain falls	Class FEM	Lifting speed m/min.	Duty rating % ED	Weight
--	ED06S	0,06	3	ED single speed	315	1	1Am	20,1	30	11,5
--	ED06ST	0,06	3	ED dual speed	315	1	1Am	20.1/4.0	30	12
--	EDC06SD	0,06	1,8	EDC dual speed	945	1	1Am	20,1/4,0	30	14,5
--	ED10S	0,1	3	ED single speed	315	1	1Am	12,5	30	11,5
--	ED10ST	0,1	3	ED dual speed	315	1	1Am	12.5/3.0	30	12
--	EDC10SD	0,1	1,8	EDC dual speed	945	1	1Am	12,5/3,0	30	14,5
--	ED16S	0,16	3	ED single speed	330	1	1Am	19,2	30	15,5
--	ED16ST	0,16	3	ED dual speed	330	1	1Am	19.2/4.0	30	16
--	EDC16SD	0,16	1,8	EDC dual speed	960	1	1Am	19,2/4,0	30	18,5
--	ED18S	0,18	3	ED single speed	315	1	1Am	7,7	20	11,5
--	ED18ST	0,18	3	ED dual speed	315	1	1Am	7.7/3.0	20	12
--	EDC18SD	0,18	1,8	EDC dual speed	945	1	1Am	7,7/3,0	20	14,5
--	ED24S	0,24	3	ED single speed	330	1	1Am	12,9	30	15,5
--	ED24ST	0,24	3	ED dual speed	330	1	1Am	12.9/3.0	30	16
--	EDC24SD	0,24	1,8	EDC dual speed	960	1	1Am	12,9/3,0	30	18,5
--	ED48ST	0,48	3	ED dual speed	520	2	1Am	6.4/2.0	30	21
--	ED48S	0,48	3	ED single speed	520	2	1Am	6,4	30	21

1

Add to quote

Unit C1, Harworth Industrial Estate  
Bryans Close  
Harworth  
Doncaster  
DN11 8RY

01302 756 777  
[info@certex.co.uk](mailto:info@certex.co.uk)