

Loadfast Ratchet Assemblies

Manufactured from polyester, these products are designed to resist wear and to grip loads efficiently. The straps apply pressure over a broad area and are therefore unlikely to cause damage to either sheet or load. Once tensioned the straps require little or no further adjustment. Polyester webbing is unaffected by weather, oils, grease and most chemicals. It is recommended however, that contact with strong alkalis should be avoided.

The 50mm restraint, commonly used for commercial applications is available as an endless assembly (LF1), or with D-Ring (LF2), Snap Hook (LF3) or Claw Hook (LF4). Each Loadfast Restraint is manufactured to BSEN 12195 Part 2: 2001. The larger widths (50mm & 75mm) are provided with two chafing sleeves to help reduce damage and wear to the webbing. Larger and Non Standard products are available on request.



Select a row from the table below, then click the add to quote button

Part Code	Length m	Fitting	Width mm	Packing Qty.	Max load ton	Packing Qty.
--	5	D-Ring	25	1	1	1
--	5	D-Ring	35	1	2	1
--	5	Claw Hook	35	1	2	1
08C0010	5	Claw Hook	25	1	1	1
--	6	D-Ring	50	1	5	1
08C0030	6	Claw Hook	50	1	5	1
--	6	Snap Hook	50	1	5	1
--	8	D-Ring	75	1	10	1
--	8	Claw Hook	75	1	10	1
08C0050	8	Claw Hook	50	1	5	1
--	8	Snap Hook	50	1	5	1
--	8	D-Ring	50	1	5	1
--	10	D-Ring	50	1	5	1
08C0070	10	Claw Hook	50	1	5	1
--	10	Snap Hook	50	1	5	1
08C0075	10	D-Ring	75	1	10	1
08C0076	10	Claw Hook	75	1	10	1

1

Add to quote

Unit C1, Harworth Industrial Estate
Bryans Close
Harworth
Doncaster
DN11 8RY

01302 756 777
info@certex.co.uk