

Wire Rope Clip Crosby G-450

Crosby

Based on the catalog breaking strength of wire rope, Crosby wire rope clips have an efficiency rating of 80% for 3 mm through 22 mm sizes, and 90% for sizes 24 mm through 90 mm.

Features: Wire clips to secure and form a temporary termination on site.

Material: Steel

Marking: According to standard, ID code and Manufacturer's symbol

Finish: Galvanised

Standard: EN 13411-5

Note: All sizes except 68-72 mm and 85-90 mm meet the performance requirements of EN13411.



Select a row from the table below, then click the add to quote button

Part Code	Rope diameter mm	A mm	B mm	C mm	D mm	E mm	F mm	G mm	H mm	Weight kg/100m
--	3-4	5,6	18,3	11,2	11,9	10,4	9,65	20,6	23,9	2,72
--	5	6,35	24,6	14,2	15	12,7	11,2	23,9	29,5	4,54
--	6-7	7,85	26,2	12,7	19,1	16,8	14,2	30,2	36,6	8,62
--	8	9,65	35,1	19,1	22,4	18,3	17,5	33,3	42,9	12,7
--	9-10	11,2	38,1	19,1	25,4	23,1	19,1	41,4	49,3	21,8
--	12-13	12,7	47,8	25,4	30,2	28,7	22,4	48,5	58	36,3
--	16	14,2	60,5	31,8	33,3	34	23,9	52,5	63,5	49,9
--	18-20	15,7	70	36,6	38,1	35,8	26,9	57	72	64
--	22	19,1	79	41,1	44,5	40,4	31,8	62	80,5	96
--	24-26	19,1	89	46	47,8	45,2	31,8	67	88	114
--	28-30	19,1	98,5	51	51	48,5	31,8	71,5	91	128
--	32-34	22,4	108	54	59,4	55,5	36,6	79,5	105	199
--	36	22,4	118	58,5	59,4	58,5	36,6	79,5	106	200
--	38	22,4	125	60,5	66,5	62	36,6	86,5	113	247
04E0288	41-42	25,4	135	66,5	70	67,5	41,4	92	11	319
04E0289	44-46	28,7	146	70	77,5	74,5	46	97	134	424
04E0290	48-52	31,8	164	76	86	77	51	113	149	590
--	56-58	31,8	181	81	98,5	81	51	114	162	726
--	62-65	31,8	195	87,5	105	93,5	51	119	168	862
--	68-72	31,8	211	90,5	111	124	51	127	175	1 043
--	75-78	38,1	233	98,5	121	119	60,5	149	194	1 406
--	85-90	38,1	273	114	140	152	60,5	157	213	1 814

* Electro-plated U-Bolt and Nuts. ** 70mm and 89mm base is made of cast steel.

1

Add to quote

