

Ferrule T Talurit™



The turnback ferrule system is easy to use. It is quick, safe and has proved itself to be totally reliable. The ferrules are thoroughly specified and very well defined for many different wire rope applications.

The ferrules can be used for fibre core single layer wire ropes, steel core single layer wire ropes, rotation resistant wire ropes and spiral strand ropes.

Material: Aluminum

Marking: According to standard

Standard: EN 13411-3

except size range

Note: See the manufacturer's product data sheet below for guidance on dimension selection.



Select a row from the table below, then click the add to quote button

Part Code	Ferrule size	Length mm
--	3	14
--	4	18
--	5	23
--	6	27
--	7	32
--	8	36
--	9	40
--	10	45
--	11	50
--	12	54
--	13	59
--	14	63
--	16	72
--	18	81
--	2.5	12
--	20	90
--	22	99
--	24	108
--	26	117
--	28	126
--	3.5	16
--	30	135
--	32	144
--	34	153
--	36	162
10.01T38	38	171
10.01T045	4.5	20
10.01T40	40	180
10.01T44	44	198
10.01T48	48	216
10.01T52	52	234
10.01T56	56	252
10.01T065	6.5	29
10.01T60	60	270

*Diameter after pressing, see instruction.
Length is after pressing.*

1

Add to quote

info / downloads

info / downloads

Select ▼

Download

Unit C1, Harworth Industrial Estate
Bryans Close
Harworth
Doncaster
DN11 8RY

[01302 756 777](tel:01302756777)
info@certex.co.uk